

**Complete kit with cover, brush, 2xUSB charger, 3 schuko
socket outlets and plate for 2 RJ45 connectors white S400
Indesk**

REF. 44523020-130



BASIC INFORMATION

DESCRIPTION

Providing maximum safety in electrical systems is the raison d'être of Simon. In its 400 range, the complete kit integrated into the table stands out, featuring a cover and brush, a charger with 2xUSB, three schuko socket bases, and a plate for two RJ45 connectors in white. With an intensity of 16 A and a voltage of 250 V~, it is suitable for flush mounting in furniture and compatible with all functions of the Simon 400 Indesk series. Its dimensions are 295 x 185 x 85 mm. Among its most notable qualities are: insulation resistance of >5 MO at 500 V, Wieland® gst18i connector with three pole male aerial and a 22 cm patch cord, and dielectric strength without piercing or contouring of 2000 V at 50 Hz for one minute. It has been manufactured with a painted steel housing, anodized aluminum profile, covers, and fasteners made of self-extinguishing thermoplastic that is halogen-free, ensuring no flame propagation in the event of a fire and low toxicity in case of smoke emissions.

FINISH

White

MATERIAL

Metal

COMPATIBILITY

Can be combined with the range of Electric Cabling from Simon.

PACKAGING CONTENTS

Pre-wired profile, enclosure, fastening claws and installation manual.

ETIM CLASS

EC002759

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

INSULATION RESISTANCE (V-MΩ)

>5 MΩ a 500 V

RECESS DIMENSION (MM)

273 x 175 mm (± 2mm)

PROTECTION AGAINST DIRECT ACCESS OF CONTACTS

No

CURRENT (A)

16 A

NUMBER OF RJ45 WINDOWS

2

PROTECTION AGAINST ENTRY OF DUST AND SMALL OBJECTS

Yes, thanks to the included protective cover and cable outlet with brush

IP RATING

IP30

SNAP-FIT RJ45 PLATES

Keystone I, II and Systimax

DIELECTRIC STRENGTH

No holes or contours, with 2000V at 50 Hz for 1 minute

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

SNAP-FIT TYPE

Keystone I, II and Systimax

MAX TEMP DURING CONSTRUCTION WORK (°C)

+60° C

TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 to 60° C

NUMBER OF SOCKETS

3 sockets for standard current circuit

NUMBER OF USB CHARGERS

1

FORMAT

Schuko

TYPE OF POWER SUPPLY CONNECTOR

Wieland® GST 18i male 3-pole overhead connector with 22 cm patch cord

VERSION

5 elements

HEAT RESISTANCE (°C)

+70°C (according to standard IEC 60670)

RAL

9016

VOLTAGE (V~)

250 V~

INSTALLATION AND MAINTENANCE

CABLING ACCESS

With brush

CLAW RANGE OF OPERATION (MM)

Between 20 and 40 mm

NUMBER OF COVER OPENING POSITIONS

1

EXTINGUISHING (°C)

+70 °C (according to standard IEC 60670)

TYPE OF FASTENING

By tightening existing clamps in the fastening bracket.

REMOVAL OF THE FRAME

Only with tool

INSTALLATION TYPE

Suitable for recessed mount in furniture.

OPENING ORIENTATION

At 45°

SECURING POSSIBILITIES

Using supplied claws or screws in the available holes

MOUNTING WITHOUT ACCESSORIES

Supplied with all necessary materials for installation.

REGULATIONS

REGULATIONS

Directiva 2014/35/UE LVD;Directiva 2011/65/UE RoHS;EN 50581:2012;EN 60670-1:2005;EN 60670-1:2005 A1:2013;IEC 60884-1 Ed 3.2;

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053208243

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING GROSS WEIGHT

2.155

PRODUCT NET WEIGHT

2.155

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053208243

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

275

PACKAGING WIDTH

195

PACKAGING LENGTH

90

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

4826250

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

0

PACKAGING NET WEIGHT

2.155

PACKAGING WEIGHT UNIT

KGM