Reduced depth floor box for 2 double elements for installation in technical or pavement floor gray Simon Cima

REF. **SF200/1**



BASIC INFORMATION

FINISH
Grey

MATERIAL
Various

COMPATIBILITY
With Simon Cima and Simon 27 Play/Simon K45 mechanisms (via adapter)

ETIM CLASS
EC000024

TECHNICAL INFORMATION

NUMBER OF CLAMP-HOLDER HOLES
4

HEAT RESISTANCE (°C)
+125 °C (in accordance with standard IEC 60695-10-2)

IK CLASSIFICATION
08

KIT AVAILABILITY
No

MAINTENANCE
Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

MAXIMUM LOAD (KG)
400kg

NUMBER OF PRE-PUNCHED HOLES 55 X 20 MM
4

RAL
7011

RECESS DIMENSION (MM)
250 x 178 mm

INSTALLATION AND MAINTENANCE

REMOVAL OF COMPONENTS
Only with tool

NUMBER OF COVER OPENING POSITIONS
2

EXTINGUISHING (°C)
+850 °C / 30 seconds (GWFI in accordance with standard IEC 60695-2-11)

REMOVAL OF THE FRAME
Only with tool

CAN BE INSTALLED IN TRAY
Plástica

LOGISTICS INFORMATION

UNITARY EAN CODE
8421053090510

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING LENGTH
0

UNITARY PACKAGING VOLUME
0

UNITARY PACKAGING GROSS WEIGHT
1.25

PRODUCT NET WEIGHT
1.25

UNITARY PACKAGING WEIGHT UNIT
KGM

PACKAGING EAN
8421053090510

UNITS CONTAINED PACKAGING
1

PACKAGING HEIGHT
80

PACKAGING WIDTH
210

PACKAGING LENGTH
280

PACKAGING MEASUREMENT UNIT
MMT

PACKAGING VOLUME
0.047

PACKAGING VOLUME UNIT
HLT

PACKAGING GROSS WEIGHT
0

PACKAGING NET WEIGHT
1.25

PACKAGING WEIGHT UNIT
KGM