

Voice and data angled plate with dust cover for 1 element and 1 RJ45 connector category 6 UTP aluminium Simon K45

REF. K8096U/8



BASIC INFORMATION

DESCRIPTION

The maximum security and the most innovative design are hand in hand in the angled voice and data plate with dust cover for an element and an RJ45 connector category 6 UTP aluminium finish of the range Simon K45, an element with dimensions of 45 x 45 x 46 " 5 mm and cabling 22-24 AWG. Metallic components with self-extinguishing and halogen-free thermoplastic insulation. make up its structure, which guarantees no flame propagation in case of fire and low toxicity in the event of smoke generation. Suitable for surface-mounted and recess, this is an element that each day it is the most sold between individuals and professionals in the industry. Finally, in case of combining the voice and data plate in vertical enclosures, such as mini columns, columns, Teleblock, channels, mechanism holders, you must use the 90° positioner (ref. K66) to guide the plate into a vertical position.

FINISH

Aluminium

COMPATIBILITY

Simon K45 enclosures for installation in the wall, floor, ceiling and furniture and Simon 500 Cima enclosures (need to be combined with the K45 to 500 Cima adaptor ref.50012088-033)

PACKAGING CONTENTS

Voice and data tilted plate with dust cover, direct module for snap-fit connector and RJ45 category 6 UTP connector

ETIM CLASS

EC000018

REMARKS

When combining the voice and data plate in vertical housings (mini columns, columns, Teleblock, channels, mechanism holders, etc.) you must use the 90° positioner (ref. K66) to guide the plate into a vertical position.

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

CABLE SECTION ADMITTED (MM)

22-26 AWG wiring

AVAILABLE IN

Plate with 1 and 2 RJ45 connectors

RJ45 CONNECTION

With insertion tool

CONNECTOR CHARACTERISTICS

Category 6 UTP

RJ45 CONNECTORS

Included in voice and data plate

MAX TEMP DURING CONSTRUCTION WORK (°C)

+60° C

DUST PROTECTION

Yes

DUST SHUTTER

Yes

FORMAT

RJ45

IP RATING

IP20

KIT AVAILABILITY

No

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 to 60° C

NUMBER OF MODULES

Half

PLATE TYPE

Angled

RJ45 ADAPTOR MODULE

Supplied with the voice and data plate

SNAP-FIT RJ45 PLATES

Keystone I, II, ATT®/Avaya®

SNAP-FIT TYPE

Keystone I, II, ATT®/Avaya®

VERSION

Single

INSTALLATION AND MAINTENANCE

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Universal, specific Simon K45 and specific Simon 500 Cima using adaptor (ref.50012088-033)

INSTALLATION DIRECTION

Vertical according to the direction of the mechanisms

INSTALLATION TYPE

Suitable for surface and flush mounting

REMOVAL OF THE PLATE

Only with tool

REGULATIONS

REGULATIONS

Directive 2011/65/UE RoHS + post. mod. | EN IEC 63000:2018 | EN 50173-1:2018*1

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT

0

PRODUCT NET WEIGHT

0.029

PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING VOLUME

2871375

UNITARY PACKAGING LENGTH

0

PACKAGING EAN

8426436046320

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING VOLUME

0.3

UNITS CONTAINED PACKAGING

10

PACKAGING GROSS WEIGHT

0.26

UNITARY PACKAGING VOLUME UNIT

MMQ

PACKAGING HEIGHT

95

PACKAGING NET WEIGHT

0.29

UNITARY PACKAGING GROSS WEIGHT

0.029

PACKAGING WIDTH

155

PACKAGING WEIGHT UNIT

KGM

PACKAGING LENGTH

195