


Switch for blinds 10A 250V~ with 3 positions with fast terminal connection ivory Simon 24 Harmonie

REF. 2410333-031



BASIC INFORMATION

FINISH

Ivory

PACKAGING CONTENTS

Mechanism

COMPATIBILITY

Simon 24 Harmonie frames

ETIM CLASS

EC000044

TECHNICAL INFORMATION

AVAILABLE MARKET

CE, except for Spain, UK, Poland, Portugal, Andorra and Russia

CABLE SECTION ADMITTED (MM)

From 1,5 to 2,5 mm

NUMBER OF POSSIBLE ELEMENTS

1 element

NUMBER OF FUNCTIONAL POSITIONS

3

IK CLASSIFICATION

01

CURRENT (A)

10 A

IP RATING

IP20

TYPE OF MECHANISM

Rocker

OPERATING TEMPERATURE RANGE (°C)

5 - 40 °C

STORAGE TEMPERATURE RANGE (°C)

-25 - 50 °C

VERSION

Single

VOLTAGE (V~)

250 V~

INSTALLATION AND MAINTENANCE

CABLE STRIPPING NECESSARY (MM)

11

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Universal

TYPE OF TERMINAL CONNECTION - FUNCTION 1

Fast

CLAW

Push&Go

INSTALLATION TYPE

Flush-mounted or surface-mounted

REGULATIONS

REGULATIONS

NM 06.6.001-2015

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053189092

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING GROSS WEIGHT

0.065

PRODUCT NET WEIGHT

0.056

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053348185

UNITS CONTAINED PACKAGING

10

PACKAGING HEIGHT

92

PACKAGING WIDTH

91

PACKAGING LENGTH

336

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

2812992

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

0.647

PACKAGING NET WEIGHT

0.56

PACKAGING WEIGHT UNIT

KGM