# IP66 Mechanism holder and manual frame with 2 schuko and 2 RJ45 6 UTP

REF. **KFH216U/72**



## BASIC INFORMATION

### DESCRIPTION

Simon completely renews its range of watertight floor boxes for indoor and outdoor environments. This is a manual closure mechanism frame with 2 schuko sockets and 2 RJ45 category 6 UTP connectors. In combination with its base, it allows for installation in raised floors or pavements. The product design, coupled with its stainless steel manufacturing, ensures a robust, solid, and secure installation as it withstands a water jet of 1 kg/cm$^2$ from any direction, achieving a protection rating of IP66 when the lid is closed. It also supports a maximum load of 2000 kg and has an IK08 impact resistance. It maintains an optimal bending radius for high-category voice and data connections. Our accessory for connecting devices with the lid closed is available, allowing us to keep our connections active with an IP54 (see reference KFA1001), the ability to level our box in case of an uneven substrate (see reference KFA1003), or the capacity to link multiple boxes (see reference KFA1002).

### FINISH

Steel

### COMPATIBILITY

K45 Solutions

### MATERIAL

Polycarbonate

### ETIM CLASS

EC000024

### REMARKS

To complete the installation of the product, it must be combined with a tray for the IP66 waterproof floor box.

## TECHNICAL INFORMATION

### FORMAT

Schuko

### IP RATING

IP66

### MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

### IK CLASSIFICATION

08

### KIT AVAILABILITY

Yes

### CURRENT (A)

16 A

### MAXIMUM LOAD (KG)

2000 Kg - Closed box | 250 Kg - Open box

## INSTALLATION AND MAINTENANCE

REMOVAL OF COMPONENTS

Only with tool

NUMBER OF COVER OPENING POSITIONS

1

EXTINGUISHING (ºC)

+650 ºC (according to standard IEC 60670)

REMOVAL OF THE FRAME

Only with tool

REMOVAL OF THE SOCKET

Only with tool

TYPE OF TERMINAL CONNECTION - FUNCTION 1

Screw

## REGULATIONS

REGULATIONS

Dir. 2014/35/UE LVD|Dir. 2011/65/UE RoHS + post. mod.|EN 50173-1:2018|EN 60670-23:2008|EN IEC 63000:2018 |IEC 60884-1 Ed 3.2|UNE 20315-1-1:2017|UNE 20315-1-2:2017|

## LOGISTICS INFORMATION

UNITARY EAN CODE
8421053334911

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING LENGTH
0

UNITARY PACKAGING MEASUREMENT UNIT
MMT

UNITARY PACKAGING VOLUME
0

UNITARY PACKAGING VOLUME UNIT
MMQ

UNITARY PACKAGING GROSS WEIGHT
0.795

PRODUCT NET WEIGHT
0.702

UNITARY PACKAGING WEIGHT UNIT
KGM

PACKAGING EAN
8421053334911

UNITS CONTAINED PACKAGING
1

PACKAGING HEIGHT
114

PACKAGING WIDTH
125

PACKAGING LENGTH
180

PACKAGING MEASUREMENT UNIT
MMT

PACKAGING VOLUME
2565000

PACKAGING VOLUME UNIT
MMQ

PACKAGING GROSS WEIGHT
0.795

PACKAGING NET WEIGHT
0.702

PACKAGING WEIGHT UNIT
KGM