

Multisensor True Presence HF+LUX recessed box IP white IP20

REF. 89220524-230



BASIC INFORMATION

DESCRIPTION

Real presence and light multisensor for flush mounting. The recommended installation height is 2.8 m, with a maximum height of 12 m. It has a detection angle of 360° and an opening angle of 160°. The tangential detection range is 15 m and the radial detection range is 15 m.

The light regulation range is 2 - 2000 lux. The detector configuration is carried out via Bluetooth and IP application.

It has a TEACH operating mode. Possibility of interconnection between sensors via Bluetooth. The control protocol is IP.

The power supply voltage is standard POE. The operating temperature of the detector is: 0 - 50 °C.

White finish, IP protection grade 20 and dimensions: 123 x 123 x 53 mm.

5-year warranty.

For more product information, visit STEINEL website by clicking [here](#)

FINISH

White

COMPATIBLE WITH MECHANICAL PUSH BUTTON

No

ETIM CLASS

EC001582

COMPATIBILITY

Simon Sensor Pro

TECHNICAL INFORMATION

IP RATING

IP20

RAL

9010

POWER SUPPLY (V~)

Standard PoE (IEEE 802.3af)

CONTROL

IP

INSTALLATION AND MAINTENANCE

MINIMUM INSTALLATION
HEIGHT

2

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053357217

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING
MEASUREMENT UNIT

MMT

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING VOLUME
UNIT

MMQ

UNITARY PACKAGING GROSS
WEIGHT

0.243

PRODUCT NET WEIGHT

0.143

UNITARY PACKAGING WEIGHT
UNIT

KGM

PACKAGING EAN

8421053357217

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

162

PACKAGING WIDTH

100

PACKAGING LENGTH

143

PACKAGING MEASUREMENT
UNIT

MMT

PACKAGING VOLUME

2316600

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

0.243

PACKAGING NET WEIGHT

0.143

PACKAGING WEIGHT UNIT

KGM