

Downlight 725.22 Flush mount NW General 1-10V Aluminium

REF. 72522133-984



BASIC INFORMATION

DESCRIPTION

This downlight 725.22 is designed to offer a type of general lighting. It is characterized by a neutral colour temperature (3900 K) and is suitable for its placement in transit areas such as corridors, but also for general office lighting or commercial establishments. Another of its qualities is its light output of 2300 lm / 24 W and also has a service life of up to 30,000 hours if it gives the maintenance. The downlight is in aluminium colour and weight 1.25 kg. It is suitable for flush mounting in the ceiling, in the same way that all the products in this range, it is ideal to do it in environments with a temperature range between -15 and 40°C, in order to ensure optimum preservation. Consists of 1-10 V control. The product is suitable for installation in spaces and restaurants or hospitals, providing a uniform lighting.

APPLICATION

General lighting

PACKAGING CONTENTS

1 unit

TECHNICAL INFORMATION

FREQUENCY

50 - 60 Hz

DRIVER INCLUDED

Yes

LUMENS (LM)

2300 lm

IP RATING

IP20

ELECTRICAL CLASS

Type 1

LUMENS/W

2300 lm/24W

OPERATING TEMPERATURE RANGE (°C)

-15 - 40 °C

INTEGRATED POWER SUPPLY

Yes

OPTICS

General

POWER SUPPLY (V~)

100/240 V~

L70 (°C)

30,000 h at 25 °C

PHOTOBIOLOGICAL CLASSIFICATION

Exempt category

COLOR TEMPERATURE (K)

3900 K

LIGHT BEAM APERTURE ANGLE (°)

120°

POWER (W)

24 W

CONTROL

1-10 V

COLOR TYPE

NW

SERVICE LIFE

30.000 h

CRI

80

LIGHTING EFFICIENCY (LM/W)

96 lm/W

CHROMATICS CRI ICONS

CRI
80

INSTALLATION AND MAINTENANCE

INSTALLATION ALTERNATIVES

Surface

INSTALLATION TYPE

Flush mount

MINIMUM INSTALLATION HEIGHT

107

TYPE OF TERMINAL CONNECTION - FUNCTION 1

Quick connector

REGULATIONS

WARRANTY

3 years 30,000 h

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053116753

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING GROSS WEIGHT

1.25

PRODUCT NET WEIGHT

1.25

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053116753

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

70

PACKAGING WIDTH

250

PACKAGING LENGTH

250

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

4.375

PACKAGING VOLUME UNIT

DMQ

PACKAGING GROSS WEIGHT

0

PACKAGING NET WEIGHT

1.25

PACKAGING WEIGHT UNIT

KGM