

## Floor trunking 2m and 240x34mm with 4 compartments

REF. TF11193/8



### BASIC INFORMATION

#### DESCRIPTION

The DCS TF11193/8 floor trunking is the most robust solution in the range, ideal for floor installations requiring high resistance. With a 240x34 mm profile, it is made of anodized aluminum and offers IK10 protection, ensuring durability against impacts and constant vehicle passage. Its maximum load capacity of 100 kg/cm<sup>2</sup> makes it perfect for industrial warehouses, parking lots, and mechanical workshops. The installation is easily carried out on non-combustible floors, ensuring compliance with UNE-EN 50085-1, and allows access to wiring with tools for safe and efficient maintenance.

#### FINISH

Aluminium

#### MATERIAL

Aluminium

#### ETIM CLASS

EC000722

## TECHNICAL INFORMATION

### IK CLASSIFICATION

10

### IP RATING

IP4X

### KIT AVAILABILITY

No

### MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

### MAXIMUM LOAD (KG)

100 Kg/cm<sup>2</sup>

### MONOBLOCK

No

### RAL

7035

## INSTALLATION AND MAINTENANCE

### REMOVAL OF COMPONENTS

Only with tool

### REMOVAL OF COVER

Only with tool

### REMOVAL OF THE FRAME

Only with tool

## LOGISTICS INFORMATION

### UNITARY EAN CODE

8421053264188

### UNITARY PACKAGING HEIGHT

0

### UNITARY PACKAGING WIDTH

0

### UNITARY PACKAGING LENGTH

0

### UNITARY PACKAGING VOLUME

0

### UNITARY PACKAGING GROSS WEIGHT

0

### PRODUCT NET WEIGHT

4.15

### UNITARY PACKAGING WEIGHT UNIT

KGM

### PACKAGING EAN

8426436028067

### UNITS CONTAINED PACKAGING

4

### PACKAGING HEIGHT

69

### PACKAGING WIDTH

319

### PACKAGING LENGTH

2030

### PACKAGING MEASUREMENT UNIT

MMT

### PACKAGING VOLUME

44682330

### PACKAGING VOLUME UNIT

MMQ

### PACKAGING GROSS WEIGHT

17.7

### PACKAGING NET WEIGHT

16.6

### PACKAGING WEIGHT UNIT

KGM