

Auxiliary cover for adapting K45 mini columns to floor trunking distribution baseboards stainless steel Simon Trunking

REF. ALKA02/8



BASIC INFORMATION

DESCRIPTION

Auxiliary cover to fit K45 mini columns to floor trunking distribution baseboards made of stainless steel, and belonging to the series Simon Trunking. Being made of stainless steel, it has a metallic finish, which is fully created for that adapts to any style of decoration, contributing to the spaces brightness and a touch modern. We recommend that, if you want to maintain this cover properly clean and shine, the cleaning will be done only with a soft and dry cloth that does not cause any type of scratching to the stainless steel, and it is also necessary to take into account the fact that you never be of clean with abrasive cloths or cleaners that you use chlorine in its formulation, as this may damage the material. It is a cover specially designed to adapt K45 mini columns on a distribution baseboard. If you use only the baseboard for the distribution of floor trunking, it is advisable to use the upper trim cover for distribution baseboard KTA904 / 8.

FINISH

Metal

COMPATIBILITY

Distribution sockets Simon Trunking

PACKAGING CONTENTS

Auxiliary cover to adapt K45 mini columns and installation manual

MATERIAL

Stainless steel

ETIM CLASS

EC002649

REMARKS

Specifically designed cover to adapt K45 mini columns on a distribution plinth. In the event of only using the distribution plinth for floor trunking, it is advisable to use the upper trim cover for the KTA904/8 distribution baseboard.

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

DIELECTRIC STRENGTH

Without perforation or
contournement with 2000 V at
50H during 1 minute

MAX TEMP DURING CONSTRUCTION WORK (°C)

+120° C

EARTHING RESISTANCE

< 0.05 ?

ELECTRICAL PROPERTIES

With electrical continuity

HEAT RESISTANCE (°C)

+850°C (according rule IEC
60695-10-2)

INSULATION RESISTANCE (V-MΩ)

5 MOhms at 500 V.

IP RATING

IP4X

KIT AVAILABILITY

No

MAINTENANCE

Clean with a soft, dry cloth. Do
not use abrasive cloths or
cleaning products that contain
chlorine.

TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 to 60° C

INSTALLATION AND MAINTENANCE

REMOVAL OF COVER

Only with tool

TYPE OF FASTENING

Using screws

INSTALLATION DIRECTION

Horizontal

REGULATIONS

REGULATIONS

Directive 2014/35/UE LVD + EN 50085-2-2:2008

LOGISTICS INFORMATION

UNITARY EAN CODE

8426436038042

PRODUCT NET WEIGHT

0.08

PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING VOLUME

422500

UNITARY PACKAGING WIDTH

0

PACKAGING EAN

8426436038042

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING LENGTH

0

UNITS CONTAINED PACKAGING

1

PACKAGING GROSS WEIGHT

0.1

UNITARY PACKAGING VOLUME

422500

PACKAGING HEIGHT

25

PACKAGING NET WEIGHT

0.08

UNITARY PACKAGING VOLUME UNIT

MMQ

PACKAGING WIDTH

130

PACKAGING WEIGHT UNIT

KGM

UNITARY PACKAGING GROSS WEIGHT

0.08

PACKAGING LENGTH

130