ARCH Downlight X-Less Accessory Square 1-10 V

REF. **91591119-999**



BASIC INFORMATION

APPLICATION
Domestic,Office,Retail,Hotel,Contract

PACKAGING CONTENTS
1 Unit

PACKAGING DIMENSIONS (MM)
90x115x169 mm

TECHNICAL INFORMATION

FREQUENCY
50 - 60 Hz

IP RATING
IP20 / IP43

OPERATING TEMPERATURE RANGE (ºC)
0 - 35 ºC

POWER SUPPLY (V~)
110/240 V~

CONTROL
1-10 V,Push Dim

COS Φ
0.94

DIRECTIONAL
No

DRIVER INCLUDED
No

ELECTRICAL CLASS
II

ENERGY EFFICIENCY
A+

LIGHTING EFFICIENCY (LM/W)
111 lm/W

PHOTOBIOLOGICAL CLASSIFICATION
Class II

POWER FACTOR (Φ)
> 0,9

INSTALLATION AND MAINTENANCE

INSTALLATION ALTERNATIVES
Flush-mounted, Surface-mounted

INSTALLATION TYPE
Trimless

REGULATIONS

EAC MARKED
Yes

ECORRAE MARKED
Yes

WARRANTY
5 years

LOGISTICS INFORMATION

UNITARY EAN CODE
8436547036752

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING LENGTH
0

UNITARY PACKAGING VOLUME
2.475

UNITARY PACKAGING VOLUME UNIT
DMQ

UNITARY PACKAGING GROSS WEIGHT
2

PRODUCT NET WEIGHT
2

UNITARY PACKAGING WEIGHT UNIT
KGM

PACKAGING EAN
8436547036752

UNITS CONTAINED PACKAGING
1

PACKAGING HEIGHT
100

PACKAGING WIDTH
160

PACKAGING LENGTH
175

PACKAGING MEASUREMENT UNIT
MMT

PACKAGING VOLUME
0.028

PACKAGING VOLUME UNIT
HLT

PACKAGING GROSS WEIGHT
0.326

PACKAGING NET WEIGHT
2

PACKAGING WEIGHT UNIT
KGM