

729.61 120X30 Low Glare Dip Switch

REF. 72961033-687



BASIC INFORMATION

DESCRIPTION

Modular LED luminaire 729, 1195x295mm aluminium body with microprismatic diffuser for uniform glare-free lighting (UGR<19). 3000K / 5000K CCT, CRI80, 3900lm, 114 lm/W. On-Off driver. Installation: suspended, recessed or surface mounted.

FINISH

White

APPLICATION

General lighting

MATERIAL

Aluminium

ETIM CLASS

EC002892

TECHNICAL INFORMATION

FREQUENCY

50 - 60 Hz

OPERATING TEMPERATURE RANGE (°C)

-20...+35

CONTROL

On/Off

IP RATING

IP20

POWER SUPPLY (V~)

220/240 V~

OPTICS

Diffused

REGULATIONS

REGULATIONS

Dir. 2014/35/UE LVD | Dir. 2014/30/UE EMC | Dir. 2009/125/EC ErP (Reg. UE 2019/2020) | Dir. 2009/125/EC ErP (Reg. UE 2019/2015) | Dir. 2011/65/UE RoHS + post. mod. | EN 60598-2-2:2012 | EN IEC 55015:2019 + A11:2020 | EN 62493:2015 | EN 61547:2009 | EN 62717:2017 + A2:2019 | EN IEC 61000-3-2:2019 + A1:2021*1 | EN IEC 63000:2018 | EN 61000-3-3:2013 + A1:2019 + A2:2021

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053370186

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING GROSS WEIGHT

2

PRODUCT NET WEIGHT

1.75

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053370186

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

35

PACKAGING WIDTH

390

PACKAGING LENGTH

1220

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

16653000

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

0

PACKAGING NET WEIGHT

1.75

PACKAGING WEIGHT UNIT

KGM