

LOOP wall-mounted luminaire 3000 K Black

REF. 91229954-388



BASIC INFORMATION

BODY MATERIAL

Die-cast aluminium

PACKAGING CONTENTS

1 Unit

APPLICATION

Domestic, Office, Retail, Hotel, Contract

PACKAGING DIMENSIONS (MM)

16x224x171 mm

TECHNICAL INFORMATION

IP RATING

IP20

DRIVER INCLUDED

No

LIGHTING EFFICIENCY (LM/W)

hasta 18 lm/W

OPERATING TEMPERATURE RANGE (°C)

0 - 35 °C

ELECTRICAL CLASS

II

LUMENS (LM)

77 lm

RAL

9005

ENERGY EFFICIENCY

A+

NUMBER OF LUMINAIRES

1

COLOR TEMPERATURE (K)

3000 K

L70 (°C)

20000h at 25°C

MACADAM STEPS

<3 Step MacAdam

CRI

80

LIGHT BEAM APERTURE ANGLE (°)

112°

OPTICS

General 112°

DIRECTIONAL

Yes

COLOR TYPE

NW

INSTALLATION AND MAINTENANCE

INSTALLATION TYPE

Trimless

REGULATIONS

EAC MARKED

Yes

ECORRAE MARKED

No

WARRANTY

3 years

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING WIDTH

0

PACKAGING EAN

8436547041893

PACKAGING VOLUME

4627350

UNITARY PACKAGING LENGTH

0

UNITS CONTAINED PACKAGING

1

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING VOLUME

0

PACKAGING HEIGHT

116

PACKAGING GROSS WEIGHT

0.39

UNITARY PACKAGING GROSS WEIGHT

0.6

PACKAGING WIDTH

171

PACKAGING NET WEIGHT

0.35

PRODUCT NET WEIGHT

0.35

PACKAGING LENGTH

224

PACKAGING WEIGHT UNIT

KGM