

Luminaire R10 BT Mesh 8,5W 4000K with detector 8m HF+LUX white IP40

REF. 89391600-084



BASIC INFORMATION

DESCRIPTION

Luminaire with integrated HF detector and Bluetooth connectivity. The power is 8.5 W, the luminous flux is 1053 lm, and the color temperature is 4000 K. The maximum installation height is 4m, and the installation is surface-mounted. The detection range is 10m, and the detection angle is 360°. The brightness regulation range is 2 - 2000 lux, and the timing range is 5 s - 60 min. The configuration of the luminaire is done via a Bluetooth application. Possibility of interconnection between luminaires through Bluetooth mesh. The power supply voltage is 220 - 240 VAC. The operating temperature is: -20 - 40 °C. Protection grade IP 40 and IK 7, and dimensions: Ø 300 x 55 mm. 5-year warranty.

For more product information, visit STEINEL website by clicking [here](#)

FINISH

White

ETIM CLASS

EC002892

TECHNICAL INFORMATION

FREQUENCY

50 - 60 Hz

IP RATING

IP40

IK CLASSIFICATION

07

POWER SUPPLY (V~)

220/240 V~

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053343234

UNITARY PACKAGING GROSS WEIGHT

1.779

PACKAGING LENGTH

370

UNITARY PACKAGING HEIGHT

0

PRODUCT NET WEIGHT

1.089

PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING VOLUME

20535000

UNITARY PACKAGING LENGTH

0

PACKAGING EAN

8421053343234

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING MEASUREMENT UNIT

MMT

UNITS CONTAINED PACKAGING

1

PACKAGING GROSS WEIGHT

1.779

UNITARY PACKAGING VOLUME

0

PACKAGING HEIGHT

370

PACKAGING NET WEIGHT

1.089

UNITARY PACKAGING VOLUME UNIT

MMQ

PACKAGING WIDTH

150

PACKAGING WEIGHT UNIT

KGM