Aluminium bracket Ofiblock Compact for 9 elements white Simon K45

REF. **KFC109/9**



BASIC INFORMATION

DESCRIPTION

Available in white colour, the Ofiblock Compact aluminium profile of 9 elements of the line, Simon K45 measures 54x450x54 mm and a space of 9 modules. It is a profile that has been specially designed to allow the convergence of solutions (energy, voice, data and multimedia) using a lesser depth, to obtain a final result much more compact and manageable. This piece has been made with the best materials of the market, as it has a profile made in anodised aluminium, while the side covers in self-extinguishing thermoplastic and they are fully halogen-free to ensure no flame spread in case of fire is the case of fire, together with a toxicity extremely low of the emissivities of smoke. You can find this and other products related in the exclusive and wide line of the products that make up the series Simon K45.

FINISH

White

MATERIAL

Metal

COMPATIBILITY

Simon K45 range functions and possible to combine with the Simon Electrical Wiring range.

PACKAGING CONTENTS

Ofiblock Compact aluminium profile, 1 ground connection, 1 blind plate, 1 side cover with direct cable entry, cabling gland, 1 blind side cover, screws and installation manual.

REMARKS

More compact profile to allow convergence of energy, voice, data and multimedia solutions at a lesser depth.

TECHNICAL INFORMATION

AVAILABLE MARKET
CE

AVAILABLE IN
Available in 2, 3, 4, 5, 6, 7, 8, 9 and 10 element versions

MAX TEMP DURING CONSTRUCTION WORK (°C)
+60° C

HEAT RESISTANCE (°C)
+125°C (according to standard IEC 60670)

INSULATION RESISTANCE (V-MΩ)
>5 MOhm at 500 V

IP RATING
IP4X

KIT AVAILABILITY
No

LINKABLE
No

MAINTENANCE
Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

TEMPERATURE RANGE DURING INSTALLATION (°C)
-5 to 60° C

NUMBER OF MODULES
9 modules

RAL
9003

NUMBER OF SIDE ENTRANCES
Up to 2 cables for each side of the profile through the ACFC02/24 cover. On request, the side cover can be supplied machined according to the customer's requirements.

SPACE FOR CABLING DISTRIBUTION
The bracket is supplied with 1 blind plate for easier internal wiring distribution.

VERSION
9 elements

INSTALLATION AND MAINTENANCE

CABLING ACCESS
Through the housings located at the sides of the profile.. Entry for fast-connection connectors, electrical cabling hose, voice, data and multimedia cabling through specific plates.

REMOVAL OF COMPONENTS
Only with tool

REMOVAL OF COVER
Only with tool

EXTINGUISHING (°C)
+850 °C (according to standard IEC 60670)

TYPE OF FASTENING
By fastening the bracket chosen and subsequent linking through the rear DIN rail on the profile.

INSTALLATION DIRECTION
Horizontal, Vertical

INSTALLATION TYPE
Suitable for installation on walls, furniture, raised floors, metal surfaces with a magnet or DIN rails.

REMOVAL OF THE PLATE
Only with tool

SCREWS REQUIRED FOR SLAB FIXING
2 (1 per side) in combination with reference KSF4 (support not supplied with profile)

SECURING POSSIBILITIES
Its design allows it to be mounted on the wall, on table-top furniture, under a desk, on a raised floor, on a metal surface with a magnet, or on a DIN rail using specific fastening accessories.

REGULATIONS

REGULATIONS

Directive 2014/35/UE LVD + EN 60670-1:2005

LOGISTICS INFORMATION

UNITARY EAN CODE

8426436039018

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING VOLUME

0.3

UNITARY PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING GROSS WEIGHT

0.445

PRODUCT NET WEIGHT

0.445

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8426436039018

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

59.5

PACKAGING WIDTH

499

PACKAGING LENGTH

54.5

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

1646700

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

0

PACKAGING NET WEIGHT

0.445

PACKAGING WEIGHT UNIT

KGM