

Angled voice and data plate with dust cover for 1 element with 1 RJ45 category 6 UTP aluminium Simon 500 Cima

REF. 50002081-033



BASIC INFORMATION

DESCRIPTION

Thanks to the angled voice and data plate with dust cover with 1 element and 1 RJ45 category 6 UTP, within the collection Simon 500 Cima, give the work area the elegance of avant-garde finishes in Alumnio/Exalumno. This angled plate, supports cabling 22-26 AWG and is compatible with Keystone-type ports, providing you with the higher the velocity and security in the transmission of data. Manufactured in self-extinguishing halogen-free thermoplastic, the angled plate 500 Cima, has a smaller to improve its appearance and functionality (50 x 50 x 42,5 mm) and is designed for installation in vertical or horizontal enclosures to include clips for its suitable fastening without the need of adapter. Its minimalist design with finishes in Aluminium, its size and the versatility and simplicity of installation, make the range of Simon 500 Cima inclined plates, the ideal to give your room of the major innovation, security and functionality.

FINISH

Aluminium

PACKAGING CONTENTS

Angled voice and data plate with dust cover, RJ45 connector category 6 UTP and installation manual

ETIM CLASS

EC000018

COMPATIBILITY

Simon 500 Cima enclosures

REMARKS

The plate is snap-fitted for mounting in vertical and horizontal enclosures without the need for an adaptor.

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

DUST PROTECTION

Yes

PLATE TYPE

Angled

CABLE SECTION ADMITTED (MM)

22-26 AWG wiring

FORMAT

RJ45

RJ45 ADAPTOR MODULE

Included in voice and data plate

RJ45 CONNECTION

With insertion tool

IP RATING

IP20

SNAP-FIT RJ45 PLATES

Keystone I, II, ATT®/Avaya®

CONNECTOR CHARACTERISTICS

category 6 UTP

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

SNAP-FIT TYPE

Keystone I, II, ATT®/Avaya®

NUMBER OF CONNECTORS

1

VERSION

Single

RJ45 CONNECTORS

Included in voice and data plate

TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 to 60 °C

MAX TEMP DURING CONSTRUCTION WORK (°C)

+60 °C

NUMBER OF MODULES

1

INSTALLATION AND MAINTENANCE

REMOVAL OF CONNECTOR

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Specific Simon 500 Cima

INSTALLATION DIRECTION

Vertical, corresponding with the direction of the mechanisms

INSTALLATION TYPE

Fixing by direct snap-fit, no tools needed.

REMOVAL OF THE PLATE

Only with tool

REGULATIONS

REGULATIONS

Directive 2011/65/UE RoHS + post. mod. | EN IEC 63000:2018 | EN 50173-1:2018*1

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING WIDTH

0

PACKAGING EAN

8421053097755

PACKAGING VOLUME

0.052

UNITARY PACKAGING LENGTH

0

UNITS CONTAINED PACKAGING

20

PACKAGING VOLUME UNIT

HLT

UNITARY PACKAGING VOLUME

0

PACKAGING HEIGHT

80

PACKAGING GROSS WEIGHT

0

UNITARY PACKAGING GROSS WEIGHT

0.028

PACKAGING WIDTH

224

PACKAGING NET WEIGHT

0.56

PRODUCT NET WEIGHT

0.028

PACKAGING LENGTH

290

PACKAGING WEIGHT UNIT

KGM

