

Floor trunking distribution baseboard with 4 pre-punched holes for 85x18 mm DCS trunking stainless steel Simon Trunking

REF. KTA804/8



BASIC INFORMATION

DESCRIPTION

Floor trunking distribution baseboards with 4 pre-punched holes for DCS 85 x 18 mm trunking in stainless steel of the series Simon Trunking. This Simon baseboard has dimensions of 140 x 140 x 30 mm, and is available with a metallic finish, to give a touch of brightness to the decoration of spaces with floor trunking, always following the latest in the world of decoration. According to the new trends, this product is suitable for installing on any floor type, whether raised or concrete. It has been designed with 4 pre-punched holes for DCS trunking of 85 x 18 mm, it also allows the distribution and branching of trunking, it facilitates the integration of K45 mini columns on the baseboard using adapter ref. ALKA02 / 8 When cleaning, we recommend that, being a product, made of stainless steel, the best way is to use a soft and dry cloth, and never with abrasive cleaners containing chlorine.

FINISH

Metal

PACKAGING CONTENTS

Distribution plinth for floor trunking, protective foam, screws and installation manual

ETIM CLASS

EC002469

MATERIAL

Stainless steel

REMARKS

Designed with 4 pre-punched holes for DCS 85 x 18 mm trunking. See table in the event of requiring a different plinth configuration for the distribution of floor trunking. In addition to allowing the distribution and branching of trunking, it facilitates the integration of K45 mini columns on the plinth base, using the adaptor ref. ALKA02/8

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

PROTECTION AGAINST ENTRY OF DUST AND SMALL OBJECTS

Yes, thanks to the inclusion of protective foam in the base of the distribution plinth.

AVAILABLE IN

1 to 3 punched holes 130 x 18 mm and 1 to 4 pre-punched holes 85 x 18 mm (see selection table)

DIELECTRIC STRENGTH

Without perforation or contourment with 2000 V at 50H during 1 minute

MAX TEMP DURING CONSTRUCTION WORK (°C)

+120° C

EARTHING RESISTANCE

< 0.05 ?

ELECTRICAL PROPERTIES

With electrical continuity

HEAT RESISTANCE (°C)

+850°C (according rule IEC 60695-10-2)

INSULATION RESISTANCE (V-MΩ)

5 MOhms at 500 V.

IP RATING

IP4X

KIT AVAILABILITY

No

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 to 60° C

VERSION

4 pre-punched holes for DCS 85 x 18 mm trunking

INSTALLATION AND MAINTENANCE

TYPE OF FASTENING

Using supplied screws

INSTALLATION DIRECTION

Horizontal

INSTALLATION TYPE

Suitable for installing on any floor type, whether raised or concrete

SCREWS REQUIRED FOR FLOOR FIXING

4

REGULATIONS

REGULATIONS

Directive 2014/35/UE LVD + EN 50085-2-4:2009

LOGISTICS INFORMATION

UNITARY EAN CODE

8426436036574

PRODUCT NET WEIGHT

0.415

PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING VOLUME

1474200

UNITARY PACKAGING WIDTH

0

PACKAGING EAN

8426436036574

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING LENGTH

0

UNITS CONTAINED PACKAGING

1

PACKAGING GROSS WEIGHT

0.415

UNITARY PACKAGING VOLUME

1474200

PACKAGING HEIGHT

63

PACKAGING NET WEIGHT

0.415

UNITARY PACKAGING VOLUME UNIT

MMQ

PACKAGING WIDTH

150

PACKAGING WEIGHT UNIT

KGM

UNITARY PACKAGING GROSS WEIGHT

0.415

PACKAGING LENGTH

156