

Flat voice and data plate with dust cover for 1 element with 2 RJ45 category 6A FTP graphite Simon 500 Cima

REF. 50001089-038



BASIC INFORMATION

DESCRIPTION

For an element with two RJ45 connectors, we have this plate of voice and data of the Simon 500 Cima series grey finish with a graphite. The plate is part of the category 6A FTP. This is the individual version with a module includes a dust shutter. The manufacturing material consists of metal components with self-extinguishing thermoplastic insulation and halogen free without elements. In this way it is possible to guarantee the security in its use, even at high temperatures. The clips to be able to receive this plate of voice and data Simon 500 Cima are included in the kit. So, you can incorporate it in both vertical and horizontal enclosures without having to use any type of specific adapter. With measures of 50 x 50 mm and a depth of 44 mm, it is one of the most functional solutions to ensure the best workplace solutions for voice and data. The wire for this plate is a cabling 22-24 AWG. The optimum maintenance of the Simon 500 Cima only requires the use of cloths dry for cleaning.

FINISH

Graphite

PACKAGING CONTENTS

Flat voice and data plate with
dust cover, 2 RJ45 category 6A
FTP and installation manual

ETIM CLASS

EC000018

COMPATIBILITY

Simon 500 Cima enclosures

REMARKS

The plate is snap-fitted for mounting in vertical and horizontal enclosures without the need for an adaptor.

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

DUST PROTECTION

Yes

NUMBER OF MODULES

1

CABLE SECTION ADMITTED (MM)

22-24 AWG wiring

DUST SHUTTER

Yes

PLATE TYPE

Flat

AVAILABLE IN

Plate for 1 and 2 RJ45

FORMAT

RJ45

RAL

7021

RJ45 CONNECTION

Without insertion tool

IP RATING

IP20

RJ45 ADAPTOR MODULE

Included in voice and data plate

CONNECTOR CHARACTERISTICS

category 6A FTP

KIT AVAILABILITY

No

SNAP-FIT RJ45 PLATES

Keystone I, II, ATT®/Avaya®

NUMBER OF CONNECTORS

2

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

SNAP-FIT TYPE

Keystone I, II, ATT®/Avaya®

RJ45 CONNECTORS

Included in voice and data plate

VERSION

Single

MAX TEMP DURING CONSTRUCTION WORK (°C)

+60 °C

TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 to 60 °C

INSTALLATION AND MAINTENANCE

REMOVAL OF CONNECTOR

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Specific Simon 500 Cima

INSTALLATION DIRECTION

Vertical, corresponding with the direction of the mechanisms

INSTALLATION TYPE

Fixing by direct snap-fit, no tools needed.

REMOVAL OF THE PLATE

Only with tool

REGULATIONS

REGULATIONS

Directive 2011/65/UE RoHS + post. mod. | EN IEC 63000:2018 | EN 50173-1:2018*1

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WEIGHT
UNIT

KGM

PACKAGING MEASUREMENT
UNIT

MMT

UNITARY PACKAGING WIDTH

0

PACKAGING EAN

8421053097830

PACKAGING VOLUME

0.052

UNITARY PACKAGING LENGTH

0

UNITS CONTAINED PACKAGING

20

PACKAGING VOLUME UNIT

HLT

UNITARY PACKAGING VOLUME

0

PACKAGING HEIGHT

80

PACKAGING GROSS WEIGHT

0

UNITARY PACKAGING GROSS
WEIGHT

0.106

PACKAGING WIDTH

224

PACKAGING NET WEIGHT

2.12

PRODUCT NET WEIGHT

0.106

PACKAGING LENGTH

290

PACKAGING WEIGHT UNIT

KGM

