

Surface mount or flush-mount wall box kit for 2 double elements with 2 double socket outlets white Simon 500 Cima

REF. 51000201-030



BASIC INFORMATION

FINISH

White

MATERIAL

Plastic

PACKAGING CONTENTS

Wall kit, metal partition wall, ground connection cable and installation manual

ETIM CLASS

EC002600

REMARKS

To complete the installation of the product, it must be combined with a flush-mount wall box (ref.51020102-039) or with a surface-mount wall box base (ref.51050002-030).

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

CABLE SECTION ADMITTED (MM)

From 1,5 to 2,5 mm

NUMBER OF CONNECTIONS PER TERMINAL

1 terminal connection for click terminal connection system and 2 terminal connections for screw terminal connection system

DIELECTRIC STRENGTH

No holes or contours, with 2000V at 50 Hz for 1 minute

MAX TEMP DURING CONSTRUCTION WORK (°C)

+60 °C in surface-mount wall installation and +90 °C in flush-mount wall installation

ELECTROMAGNETIC IMMUNITY FOR VDM WIRING

Secured by installing the metal partition wall in the housings fitted into the selected wall enclosure.

FORMAT

Schuko

HEAT RESISTANCE (°C)

+125°C (according rule IEC 60695-10-2)

INDICATOR FUNCTION

Yes

INSULATION RESISTANCE (V-MΩ)

>5MΩ at 500V

CURRENT (A)

16 A

IP RATING

IP20

LED CONSUMPTION INDICATOR (MA)

0.55

LINKABLE

Yes, using accessory included 50000996-039

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 to 60 °C

TYPE OF MECHANISM

Insertion

NUMBER OF MODULES

4

RAL

9003

RECESS DIMENSION (MM)

141 x 135 mm (* para instalação encastrada na parede)

NUMBER OF SOCKETS

2 double sockets for standard current circuits

VERSION

2 double elements

VOLTAGE (V~)

250 V~

INSTALLATION AND MAINTENANCE

CABLE STRIPPING NECESSARY (MM)

0

REMOVAL OF COVER

Only with tool

EXTINGUISHING (°C)

+850 °C / 30 seconds (GWFI in accordance with standard IEC 60695-2-11)

TYPE OF FASTENING

By direct snap-fit in the selected enclosure (no tools needed for fastening))

REMOVAL OF THE FRAME

Only with tool

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Specific Simon 500 Cima

INSTALLATION DIRECTION

Vertical, corresponding with the direction of the mechanisms

INSTALLATION TYPE

Suitable for flush mounting or surface mounting onto wall in combination with the corresponding enclosure

REMOVAL OF THE SOCKET

Only with tool

TYPE OF TERMINAL CONNECTION - FUNCTION 1

1 click connection (1 click®)

NUMBER OF TERMINALS

3 inputs and 3 outputs

REGULATIONS

REGULATIONS

Directive 2014/35/UE LVD + Directive 2011/65/UE RoHS + EN 50581:2012 + EN 60670-1:2005 + IEC 60884-1 Ed 3.2

LOGISTICS INFORMATION

| | | |
|---|---|--------------------------------------|
| UNITARY EAN CODE 8421053100189 | UNITARY PACKAGING WEIGHT UNIT KGM | PACKAGING MEASUREMENT UNIT MMT |
| UNITARY PACKAGING HEIGHT 0 | PACKAGING EAN 8421053100189 | PACKAGING VOLUME 2.104 |
| UNITARY PACKAGING WIDTH 0 | UNITS CONTAINED PACKAGING 1 | PACKAGING VOLUME UNIT DMQ |
| UNITARY PACKAGING LENGTH 0 | PACKAGING HEIGHT 75 | PACKAGING GROSS WEIGHT 0 |
| UNITARY PACKAGING VOLUME 0 | PACKAGING WIDTH 165 | PACKAGING NET WEIGHT 0.41 |
| UNITARY PACKAGING GROSS WEIGHT 0.41 | PACKAGING LENGTH 170 | PACKAGING WEIGHT UNIT KGM |
| PRODUCT NET WEIGHT 0.41 | | |

