

Angled voice and data plate with dust cover for 1 element with 1 category 5e UTP RJ45 white Simon 500 Cima

REF. 50004081-030



BASIC INFORMATION

DESCRIPTION

If you are looking for the higher the velocity of the transmission of data on its working environment, the collection Simon 500 Cima and its angled voice and data plate with dust cover for 1 element and 1 RJ45 category 5e UTP, it is the perfect solution. With finishes in white, its design is concerned, it is suitable for installation in vertical and horizontal enclosures thanks to its direct snap-fit without the need of adapters; however, it requires the MD Module to complete the assembly. Compatible with Keystone and cabling ports type 22-26 AWG, the range 500 Cima for inclined presents a bending radius ideal for the transmission of data on a fast and safe, made of thermoplastic materials self-extinguishing halogen-free, the angled plate 500 Cima, guarantees its security against fire, as it avoids the no flame propagation and toxicity by smoke. Security, innovation and for its work area.

FINISH

White

PACKAGING CONTENTS

Angled voice and data plate with dust cover, category 5e UTP RJ45 connector and installation manual

ETIM CLASS

EC000018

COMPATIBILITY

Simon 500 Cima enclosures

REMARKS

The plate is snap-fitted for mounting in vertical and horizontal enclosures without the need for an adaptor.

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

DUST PROTECTION

Yes

NUMBER OF MODULES

1

CABLE SECTION ADMITTED (MM)

22-26 AWG wiring

DUST SHUTTER

Yes

PLATE TYPE

Angled

AVAILABLE IN

Plate for 1 and 2 RJ45

FORMAT

RJ45

RAL

9003

RJ45 CONNECTION

With insertion tool

IP RATING

IP20

RJ45 ADAPTOR MODULE

Included in voice and data plate

CONNECTOR CHARACTERISTICS

Category 5e UTP

KIT AVAILABILITY

No

SNAP-FIT RJ45 PLATES

Keystone I, II, ATT®/Avaya®

NUMBER OF CONNECTORS

1

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

SNAP-FIT TYPE

Keystone I, II, ATT®/Avaya®

RJ45 CONNECTORS

Included in voice and data plate

VERSION

Single

MAX TEMP DURING CONSTRUCTION WORK (°C)

+60 °C

TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 to 60 °C

INSTALLATION AND MAINTENANCE

REMOVAL OF CONNECTOR

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Specific Simon 500 Cima

INSTALLATION DIRECTION

Vertical, corresponding with the direction of the mechanisms

INSTALLATION TYPE

Fixing by direct snap-fit, no tools needed.

REMOVAL OF THE PLATE

Only with tool

REGULATIONS

REGULATIONS

Directive 2011/65/UE RoHS + post. mod. | EN IEC 63000:2018 | EN 50173-1:2018*1

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WEIGHT
UNIT

KGM

PACKAGING MEASUREMENT
UNIT

MMT

UNITARY PACKAGING WIDTH

0

PACKAGING EAN

8421053097793

PACKAGING VOLUME

0.052

UNITARY PACKAGING LENGTH

0

UNITS CONTAINED PACKAGING

20

PACKAGING VOLUME UNIT

HLT

UNITARY PACKAGING VOLUME

0

PACKAGING HEIGHT

80

PACKAGING GROSS WEIGHT

0

UNITARY PACKAGING GROSS
WEIGHT

0.058

PACKAGING WIDTH

224

PACKAGING NET WEIGHT

1.16

PRODUCT NET WEIGHT

0.058

PACKAGING LENGTH

290

PACKAGING WEIGHT UNIT

KGM

