

French double socket outlet 16A 250V~ with safety device and screw terminal connection graphite Simon 500 Cima

REF. 50000458-038



BASIC INFORMATION

DESCRIPTION

It is a type French socket outlet double 16a 250V~ with safety device and screw terminal connection. The article is finished in graphite colour and corresponds to the Simon 500 Cima series. The socket outlet is suitable for surface or flush mounting installation. It is composed of metal elements with halogen-free thermoplastic of character self-extinguishing and which is also halogen-free. This means that the material is 100% safe in case of fire, as it prevents the spread of flames and reduces the toxicity of smoke. It measures 100 x 50 mm and has a depth of 46 mm. The piece also has been manufactured in compliance with the current regulation and is characterized by an extraordinary resistance to extreme temperatures. When it comes to maintenance, the manufacturer advises to clean it with a soft and dry cloth.

FINISH

Graphite

PACKAGING CONTENTS

Double socket outlet with cover
and installation manual

ETIM CLASS

EC000125

COMPATIBILITY

Simon 500 Cima enclosures

TECHNICAL INFORMATION

AVAILABLE MARKET CE	INSULATION RESISTANCE (V-MΩ) >5MΩ at 500V	TYPE OF MECHANISM Insertion
CABLE SECTION ADMITTED (MM) From 1,5 to 2,5 mm	CURRENT (A) 16 A	NUMBER OF MODULES 2
NUMBER OF CONNECTIONS PER TERMINAL 2 connections per terminal	IP RATING IP20	MONOBLOCK No
DIELECTRIC STRENGTH No holes or contours, with 2000V at 50 Hz for 1 minute	LINKABLE Yes, using accessory 50000996-039	NOMINAL VOLTAGE (V~) 250 V~
FORMAT French	MAINTENANCE Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.	RAL 7021
HEAT RESISTANCE (°C) +125°C (according rule IEC 60695-10-2)	TEMPERATURE RANGE DURING INSTALLATION (°C) -25 to 60 °C	NUMBER OF SOCKETS 2
INDICATOR FUNCTION No		VERSION Double

INSTALLATION AND MAINTENANCE

CABLE STRIPPING NECESSARY (MM) 12	INSTALLABLE IN FLUSH MOUNT JUNCTION BOX Specific Simon 500 Cima	REMOVAL OF THE SOCKET Only with tool
REMOVAL OF COVER Only with tool	INSTALLATION DIRECTION Horizontal, Vertical	TYPE OF TERMINAL CONNECTION - FUNCTION 1 Screw
EXTINGUISHING (°C) +850 °C / 30 seconds (GWFI in accordance with standard IEC 60695-10-2)	INSTALLATION TYPE Suitable for surface and flush mounting	NUMBER OF TERMINALS 3 inputs and 3 outputs

REGULATIONS

REGULATIONS

Dir. 2011/65/UE RoHS + post. mod. | EN IEC 63000:2018 | IEC 60884-1 Ed. 3.2 | UNE 20315-1-1:2017 | UNE 20315-1-2:2017 | DS 60884-2-D1:2023

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WEIGHT

UNIT

KGM

PACKAGING MEASUREMENT

UNIT

MMT

UNITARY PACKAGING WIDTH

0

PACKAGING EAN

8421053097403

PACKAGING VOLUME

3.525

UNITARY PACKAGING LENGTH

0

UNITS CONTAINED PACKAGING

10

PACKAGING VOLUME UNIT

DMQ

UNITARY PACKAGING VOLUME

0

PACKAGING HEIGHT

112

PACKAGING GROSS WEIGHT

0

UNITARY PACKAGING GROSS

WEIGHT

0.111

PACKAGING WIDTH

117

PACKAGING NET WEIGHT

1.11

PRODUCT NET WEIGHT

0.111

PACKAGING LENGTH

269

PACKAGING WEIGHT UNIT

KGM

