

2-way switch 10AX 250V~ for half element with built-in pilot light and fast terminal connection system ivory Simon 27 Play

REF. 27202-61



BASIC INFORMATION

DESCRIPTION

2-way switch with 10 AX current capacity and a power of 250 V~ medium element with incorporated pilot light and fast-terminal connection system with an ivory finish belonging to the Simon 27 Play series, this collection means you can install the best electronic functions in your home to control every corner of your home at your leisure, among the most outstanding functions are: Adjustment and control of lighting, programming and temperature control or centralization of blinds. Its installation has reduced the time required to carry it out thanks to the fast-terminal connection system located on the same 2-way switch. It can also be combined with the reference 2700802-037 in case of replacement of indicator light. And there is even more to its installation because you have two ways of carrying out the installation by surface-mounted or to be recessed both are suitable to perform the installation.

FINISH

Ivory

COMPATIBILITY

Simon 27 Play, Simon 27 Neos, Simon 27 Scudo, Simon 27, Simon 27 Centralisations and Simon 44 Aqua frames

PACKAGING CONTENTS

Mechanism with rocker

ETIM CLASS

EC001590

REMARKS

Can be combined with article 2700802-037 if replacing the light indicator.

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

CURRENT (A)

10 AX

NOMINAL VOLTAGE (V~)

250 V~

CABLE SECTION ADMITTED (MM)

From 1,5 to 2,5 mm

IP RATING

IP20

OPERATING TEMPERATURE RANGE (°C)

5 - 40 °C

CONSUMPTION INDICATOR (mA)

0.55 mA

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

STORAGE TEMPERATURE RANGE (°C)

-25 - 50 °C

NUMBER OF POSSIBLE ELEMENTS

Half element

TYPE OF MECHANISM

Pivoting

VERSION

Single

INDICATOR FUNCTION

Yes

INSTALLATION AND MAINTENANCE

CABLE STRIPPING NECESSARY (MM)

11

CLAW

Simon 27

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Universal, American, Small
spaces and Centralisations

INSTALLATION DIRECTION

Horizontal, Vertical

INSTALLATION TYPE

Suitable for surface and flush
mounting

TYPE OF TERMINAL CONNECTION - FUNCTION 1

Fast

REGULATIONS

REGULATIONS

Dir. 2014/35/UE LVD | Dir. 2011/65/UE RoHS + post. mod. | EN 60669-1:2018 | EN IEC 63000:2018

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT

0

PRODUCT NET WEIGHT

0.028

PACKAGING MEASUREMENT

UNIT

MMT

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING WEIGHT

UNIT

KGM

PACKAGING VOLUME

1229865

UNITARY PACKAGING LENGTH

0

PACKAGING EAN

8421053035948

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING VOLUME

1229865

UNITS CONTAINED PACKAGING

20

PACKAGING GROSS WEIGHT

0.555

UNITARY PACKAGING VOLUME

UNIT

MMQ

PACKAGING HEIGHT

53

PACKAGING NET WEIGHT

0.56

UNITARY PACKAGING GROSS

WEIGHT

0.028

PACKAGING WIDTH

105

PACKAGING WEIGHT UNIT

KGM

PACKAGING LENGTH

221

MECANISMOS SIMON 27, 28 Y 44

Mecanismos básicos / Basic switches



Interrupor unipolar / Single-pole switch
XX00101-XX



Pulsador / Push button switch
XX00150-XX



Interrupor bipolar / Double pole switch
XX00133-XX



Conmutador / 2-way switch
XX00201-XX



Conmutador cruce / Intermediate switch
XX00251-XX

Mecanismos con piloto / Pilot switches



Interrupor unipolar / Single-pole switch
XX00102-XX



Interrupor bipolar / Double pole switch
XX00134-XX



Conmutador / 2-way switch
XX00202-XX



Interrupor unipolar / Single-pole switch
XX00104-XX



Pulsador / Push button switch
XX00160-XX



Conmutador / 2-way switch
XX2700204-XX



Conmutador cruce / Intermediate switch
XX2700254-XX