

Schuko socket outlet 16A 250V~ with safety device,
indicator light and screw terminal connection aluminium
Simon K45

REF. KLS01/8



BASIC INFORMATION

DESCRIPTION

In an excellent aluminium finishes, the Schuko socket outlet KLS01 / 8 of the series Simon K45 measures 45x45 mm and has safety shutter, indicator light and screw connection. And, as we at Simon concern for always offer the greater security, this component is made of metal materials with halogen-free, self-extinguishing thermoplastic insulation to avoid that, in case of fire, the flame is spread, also offering a low toxicity in case of smoke excellent product, which is fully compatible with elements up to 250 Volt voltage and 16 Amps intensity. And do not forget to that the collection Simon K45 has been designed to offer the best security, because thanks to its constant innovation and to the use of materials of the most excellent quality, achieving meet even the most demanding performances. Neglect/Don't worry about it. of all and confident in Simon for the security of your home.

FINISH

Aluminium

COMPATIBILITY

Simon K45 enclosures for installation in the wall, floor, ceiling and furniture and Simon 500 Cima enclosures (need to be combined with the K45 to 500 Cima adaptor ref.50012088-033)

PACKAGING CONTENTS

socket plug with trim cover and indicator light

ETIM CLASS

EC000125

REMARKS

Possibility to order replacement for pin, in the event of breakage or loss, through Art.No. AC33/6

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

CABLE SECTION ADMITTED (MM)

1,5 to 2,5 mm

AVAILABLE IN

Shucko and french format

NUMBER OF CONNECTIONS PER TERMINAL

2 connections per terminal (1 input / 1 output)

DIELECTRIC STRENGTH

Without perforation or contournement with 2000 V at 50H during 1 minute

MAX TEMP DURING CONSTRUCTION WORK (°C)

+60° C

FORMAT

Schuko

HEAT RESISTANCE (°C)

+125°C (according rule IEC 60695-10-2)

INDICATOR FUNCTION

Yes

INSULATION RESISTANCE (V-MΩ)

>5M? At 500 V

CURRENT (A)

16 A

IP RATING

IP20

KIT AVAILABILITY

No

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 a 60° C

TYPE OF MECHANISM

Insertion

NUMBER OF MODULES

2 modules

MONOBLOCK

No

NUMBER OF SOCKETS

1

VERSION

Single

VOLTAGE (V~)

250 V~

INSTALLATION AND MAINTENANCE

CABLE STRIPPING NECESSARY (MM)

12

EXTINGUISHING (°C)

+850 °C / 30 seconds (GWFI in accordance with standard IEC 60695-10-2)

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Universal, specific Simon K45 and specific Simon 500 Cima using adaptor ref.50012088-033

INSTALLATION DIRECTION

Vertical according to the direction of the mechanisms

INSTALLATION TYPE

Suitable for surface and flush mounting

REMOVAL OF THE SOCKET

Only with tool

TYPE OF TERMINAL CONNECTION - FUNCTION 1

Screw

NUMBER OF TERMINALS

3 inputs / outputs

REGULATIONS

REGULATIONS

Dir. 2011/65/UE RoHS + post. mod. | EN IEC 63000:2018 | IEC 60884-1 Ed. 3.2 | UNE 20315-1-1:2017 | UNE 20315-1-2:2017 | DS 60884-2-D1:2023

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT

0

PRODUCT NET WEIGHT

0.054

PACKAGING MEASUREMENT

UNIT

MMT

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING WEIGHT

UNIT

KGM

PACKAGING VOLUME

1212505

UNITARY PACKAGING LENGTH

0

PACKAGING EAN

8421053190869

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING VOLUME

121251

UNITS CONTAINED PACKAGING

10

PACKAGING GROSS WEIGHT

0.05

UNITARY PACKAGING VOLUME

UNIT

MMQ

PACKAGING HEIGHT

49

PACKAGING NET WEIGHT

0.54

UNITARY PACKAGING GROSS

WEIGHT

0.535

PACKAGING WIDTH

101

PACKAGING WEIGHT UNIT

KGM

PACKAGING LENGTH

245