

Flat voice and data plate without dust cover for 2 RJ45 Nexans® for 1 element white Simon 500 Cima

REF. 50018189-030



BASIC INFORMATION

DESCRIPTION

With simple finishes white in colour, our plate of voice and data plate without dust cover for 2 RJ45 Nexans ® measures 50x50x11 mm and is part of the collection Simon 500 Cima. One of the safest on the market thanks to the use of thermoplastic materials in its manufacture, a material advanced thanks to its properties self-extinguishing that guarantees no flame spread in case of fire in case of fire and low toxicity levels gives occur smoke. Finally, the plate includes clips for fastening in vertical and horizontal enclosures so that it does not need any adapter. All this proves to the Simon 500 Cima series is one of the most advanced functions on the market in terms of security for your home, at Simon we concern for to offer our customers the best of the best.

FINISH

White

PACKAGING CONTENTS

Flat voice and data plate without dust cover

ETIM CLASS

EC000018

COMPATIBILITY

Simon 500 Cima enclosures

REMARKS

The plate is snap-fitted for mounting in vertical and horizontal enclosures without the need for an adaptor.

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

DUST SHUTTER

No

NUMBER OF MODULES

1

AVAILABLE IN

Plate for 1 and 2 RJ45

FORMAT

RJ45

PLATE TYPE

Flat

COMPATIBLE WITH CONNECTORS

Nexans® LANmark®-5 EVO, LANmark®-6 EVO.

IP RATING

IP20

RAL

9003

KIT AVAILABILITY

No

RJ45 ADAPTOR MODULE

Included in voice and data plate

RJ45 CONNECTORS

Not included in voice and data plate

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

SNAP-FIT RJ45 PLATES

RJ45 Nexans® connectors

MAX TEMP DURING CONSTRUCTION WORK (°C)

+60 °C

SNAP-FIT TYPE

RJ45 Nexans® connectors

DUST PROTECTION

No

TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 to 60 °C

VERSION

Single

INSTALLATION AND MAINTENANCE

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Specific Simon 500 Cima

INSTALLATION DIRECTION

Vertical, corresponding with the direction of the mechanisms

INSTALLATION TYPE

Fixing by direct snap-fit, no tools needed.

REMOVAL OF THE PLATE

Only with tool

REGULATIONS

REGULATIONS

Directive 2011/65/UE RoHS + post. mod. | EN IEC 63000:2018 | EN 50173-1:2018*1

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT

26

UNITARY PACKAGING GROSS WEIGHT

0.028

PACKAGING LENGTH

86

UNITARY PACKAGING WIDTH

58

PRODUCT NET WEIGHT

0.028

PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING LENGTH

86

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING VOLUME

0.604

UNITARY PACKAGING MEASUREMENT UNIT

MMT

PACKAGING EAN

8421053097090

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING VOLUME

129688

UNITS CONTAINED PACKAGING

10

PACKAGING GROSS WEIGHT

0

UNITARY PACKAGING VOLUME UNIT

MMQ

PACKAGING HEIGHT

26

PACKAGING NET WEIGHT

0.28

PACKAGING WIDTH

58

PACKAGING WEIGHT UNIT

KGM

