Watertight luminaire 789 18W 4000K 600

REF. **78936033-884**



BASIC INFORMATION

DESCRIPTION

Watertight luminaire for applications such as parking lots, garages, and technical areas, designed to provide uniform and comfortable lighting in circulation areas. Linear design with opal diffuser of high uniformity for homogeneous light distribution, minimizing shadows and glare. Through wiring and double connector included, allowing for a continuous run of up to 10 luminaires per line. Installation type: Surface. Optics: 120. Color temperature: 4000K. Power: 18W. Lumens: 1800lm. Efficiency: 100lm/w. Protection rating IP: IP65. Power supply: 220-240 V. 50/60 Hz. Dimensions: 655 mm x 65 mm x 65 mm.

APPLICATION

Parking,Industrial lighting,General lighting,Car park lighting

TECHNICAL INFORMATION

FREQUENCY
50 - 60 Hz

IK CLASSIFICATION
08

IP RATING
IP65

OPERATING TEMPERATURE RANGE (°C)
-25...+40

POWER SUPPLY (V~)
220/240 V~

CONTROL
On/Off

LIGHTING EFFICIENCY (LM/W)
100 lm/W

LUMENS (LM)
1800 lm

OPTICS
General

POWER (W)
18 W

INSTALLATION AND MAINTENANCE

INSTALLATION TYPE
Surface / Wall

LOGISTICS INFORMATION

UNITARY EAN CODE
8421053440230

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING LENGTH
0

UNITARY PACKAGING VOLUME
0

UNITARY PACKAGING GROSS WEIGHT
0.56

PRODUCT NET WEIGHT
0.47

UNITARY PACKAGING WEIGHT UNIT
KGM

PACKAGING EAN
8421053440230

UNITS CONTAINED PACKAGING
1

PACKAGING HEIGHT
225

PACKAGING WIDTH
300

PACKAGING LENGTH
720

PACKAGING MEASUREMENT UNIT
MMT

PACKAGING VOLUME
48600000

PACKAGING VOLUME UNIT
MMQ

PACKAGING GROSS WEIGHT
6.72

PACKAGING NET WEIGHT
0.47

PACKAGING WEIGHT UNIT
KGM