Modular Lighting 729 60x60 4000K

REF. **72950033-884**

BASIC INFORMATION

MATERIAL	APPLICATION	ETIM CLASS
Aluminium	Office	EC002892

TECHNICAL INFORMATION

FREQUENCY	POWER SUPPLY (V~)	COLOR TYPE
50 - 60 Hz	220/240 V~	NW
IP RATING	**CONTROL**	
IP20	On/Off	

INSTALLATION AND MAINTENANCE

MINIMUM INSTALLATION HEIGHT

50

REGULATIONS

REGULATIONS

Dir. 2014/35/UE LVD | Dir. 2014/30/UE EMC | Dir. 2009/125/EC ErP (Reg. UE 2019/2020) | Dir. 2009/125/EC ErP (Reg. UE 2019/2015) | Dir. 2011/65/UE RoHS + post. mod. | EN 60598-2-2:2012 | EN IEC 55015:2019 + A11:2020 | EN 62493:2015 | EN 61547:2009 | EN 62717:2017 + A2:2019 | EN IEC 61000-3-2:2019 + A1:2021*1 | EN IEC 63000:2018 | EN 61000-3-3:2013 + A1:2019 + A2:2021

LOGISTICS INFORMATION

UNITARY EAN CODE
8421053305003

UNITARY PACKAGING HEIGHT
35

UNITARY PACKAGING WIDTH
62

UNITARY PACKAGING LENGTH
69

UNITARY PACKAGING MEASUREMENT UNIT
MMT

UNITARY PACKAGING VOLUME
149730

UNITARY PACKAGING VOLUME UNIT
MMQ

UNITARY PACKAGING GROSS WEIGHT
2

PRODUCT NET WEIGHT
1.75

UNITARY PACKAGING WEIGHT UNIT
KGM

PACKAGING EAN
8421053305003

UNITS CONTAINED PACKAGING
1

PACKAGING HEIGHT
0

PACKAGING WIDTH
0

PACKAGING LENGTH
0

PACKAGING MEASUREMENT UNIT
MMT

PACKAGING VOLUME
0

PACKAGING VOLUME UNIT
MMQ

PACKAGING GROSS WEIGHT
0

PACKAGING NET WEIGHT
1.75

PACKAGING WEIGHT UNIT
KGM