

729.60 60x60 Low Glare Dip Switch DALI2

REF. 72960333-687



BASIC INFORMATION

DESCRIPTION

Modular LED luminaire 729, 595x595mm aluminium body with microprismatic diffuser for uniform glare-free lighting (UGR<19). 3000K / 5000K CCT, CRI80, 3900lm, 114 lm/W. DALI-2 driver. Installation: suspended, recessed or surface mounted.

FINISH

White

APPLICATION

General lighting

MATERIAL

Aluminium

ETIM CLASS

EC002892

TECHNICAL INFORMATION

FREQUENCY

50 - 60 Hz

IP RATING

IP20

NOMINAL VOLTAGE (V~)

220/240 V~

OPERATING TEMPERATURE RANGE (°C)

-20...+35

POWER SUPPLY (V~)

220/240 V~

CONTROL

DALI2

OPTICS

Diffused

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053370193

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING GROSS WEIGHT

2

PRODUCT NET WEIGHT

1.75

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053370193

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

35

PACKAGING WIDTH

690

PACKAGING LENGTH

690

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

16663500

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

0

PACKAGING NET WEIGHT

1.75

PACKAGING WEIGHT UNIT

KGM