

Modular luminaire 720 Advance M4 120x30 Low Glare WW DALI

REF. 72061340-683



BASIC INFORMATION

DESCRIPTION

With a warm tone WW temperature of 3000 K, the luminaire 720 modular Advance M4 of the collection Simon, will give to any space of the highest quality and functionality of light distribution with the guarantee of energy savings of its multiple LED ' s This luminaire with interface of adjustment bidirectional DALI, has optics micro prismatic system with LowGlare anti- dazzling. It has a light flux output of 3200 lm for WW and a power consumption of the luminaire 28 W, with a service life of 40,000 hours at 25 ° C to L90 and up to 100,000 hours for the L70. It is compatible, in addition, with a voltage of 230 V AC power and 50-60 Hz frequency. With a size of 1195 x 295 mm, it is designed for installation in false ceiling and hardware that, together with its finishes in white, guaranteeing the integration of the set in all types of spaces, at the same time that adds a current and minimalist style.

DIFFUSER MATERIAL

PMMA

PACKAGING CONTENTS

1 unit

APPLICATION

General lighting

ETIM CLASS

EC002892

TECHNICAL INFORMATION

FREQUENCY

50 - 60 Hz

DRIVER INCLUDED

Yes

LIGHTING EFFICIENCY (LM/W)

114 lm/W

IP RATING

IP44

ELECTRICAL CLASS

Type 2

LUMENS (LM)

3200 lm

OPERATING TEMPERATURE RANGE (°C)

40 °C maximum

INTEGRATED POWER SUPPLY

Yes

LUMENS/W

3200 lm/28W

POWER SUPPLY (V~)

230 V~

L70 (°C)

100,000 h at 25 °C

OPTICS

Microprismatic

COLOR TEMPERATURE (K)

3000 K

L90 (°C)

40,000 h at 25 °C

PHOTOBIOLOGICAL CLASSIFICATION

Exempt category

CONTROL

DALI

LIGHT BEAM APERTURE ANGLE (°)

120°

POWER (W)

28 W

CRI

82

COLOR TYPE

WW

SERVICE LIFE

50.000 h

CHROMATICS CRI ICONS

CRI
82

INSTALLATION AND MAINTENANCE

INSTALLATION ALTERNATIVES

Plaster ceiling, surface mount, concealed or semi-concealed profile.

MINIMUM INSTALLATION HEIGHT

120

INSTALLATION TYPE

False ceiling, visible hardware

TYPE OF TERMINAL

CONNECTION - FUNCTION 1

Quick connector

REGULATIONS

WARRANTY

5 years 50,000 h

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053191736

UNITARY PACKAGING WEIGHT
UNIT

KGM

PACKAGING MEASUREMENT
UNIT

MMT

UNITARY PACKAGING HEIGHT

0

PACKAGING EAN

8421053191736

PACKAGING VOLUME

23400000

UNITARY PACKAGING WIDTH

0

UNITS CONTAINED PACKAGING

1

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING LENGTH

0

PACKAGING HEIGHT

65

PACKAGING GROSS WEIGHT

0

UNITARY PACKAGING VOLUME

0

PACKAGING WIDTH

300

PACKAGING NET WEIGHT

5

UNITARY PACKAGING GROSS
WEIGHT

5.58

PACKAGING LENGTH

1200

PACKAGING WEIGHT UNIT

KGM

PRODUCT NET WEIGHT

5