

P40 socket outlet 16A with screw terminal connection 2 elements white K45

REF. K05/9



BASIC INFORMATION

FINISH

White

MATERIAL

Plastic

COMPATIBILITY

Simon K45 enclosures for installation on wall, floor, ceiling, and furniture and Simon 500 Cima enclosures (requires combination with the K45 to 500 Cima adapter ref. 50012088-030).

ETIM CLASS

EC000125

TECHNICAL INFORMATION

FORMAT

P40

IP RATING

IP20

RAL

9003

CURRENT (A)

16 A

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

INSTALLATION AND MAINTENANCE

CABLE STRIPPING NECESSARY (MM)

12

EXTINGUISHING (°C)

+850 °C / 30 seconds (GWFI in accordance with standard IEC 60695-10-2)

REMOVAL OF THE SOCKET

Only with tool

TYPE OF TERMINAL CONNECTION - FUNCTION 1

Screw

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WEIGHT
UNIT
KGM

PACKAGING MEASUREMENT
UNIT
MMT

UNITARY PACKAGING WIDTH
0

PACKAGING EAN
8421053314142

PACKAGING VOLUME
1592500

UNITARY PACKAGING LENGTH
0

UNITS CONTAINED PACKAGING
10

PACKAGING VOLUME UNIT
MMQ

UNITARY PACKAGING VOLUME
0

PACKAGING HEIGHT
245

PACKAGING GROSS WEIGHT
0.484

UNITARY PACKAGING GROSS
WEIGHT
0.04

PACKAGING WIDTH
50

PACKAGING NET WEIGHT
0.4

PRODUCT NET WEIGHT
0.04

PACKAGING LENGTH
130

PACKAGING WEIGHT UNIT
KGM

