Rocker with viewer for push button switch with indicator light function for 1 element white Simon K45

REF. **K114/9**



BASIC INFORMATION

DESCRIPTION

With finishes in colour, with the white rocker with viewer for push-button switch with indicator light function for 1 element, it is a piece suitable for position, place in surface-mounted or recess it is part of the Simon K45. This is a very used for beacon the mechanism and be able to see its position in the dark. It has measures of 45x45x10 mm and is manufactured in thermoplastic, one of the safest materials of the market to ensure that there are no flame spread in case of fire in case of fire, and a toxicity minimum of any type of smoke. Quality, security and innovation are the most important features that we can find in the series products dela Simon K45. A collection safe and efficient designed for the most demanding environments.

FINISH

White

MATERIAL

Plastic

COMPATIBILITY

Simon K45 enclosures for installation in the wall, floor, ceiling and furniture and Simon 500 Cima enclosures (need to be combined with the K45 to 500 Cima adaptor ref.50012088-030)

PACKAGING CONTENTS

Rocker and installation manual

ETIM CLASS

EC000011

REMARKS

Used to signal the mechanism and spot it in the dark

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

AVAILABLE IN

Quarter and half module versions

MAX TEMP DURING CONSTRUCTION WORK (°C)

+60° C

INDICATOR FUNCTION

Yes

IP RATING

IP20

KIT AVAILABILITY

No

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 to 60° C

NUMBER OF MODULES

Half

RAL

9003

VERSION

Single

INSTALLATION AND MAINTENANCE

REMOVAL OF COVER

Only with tool

TYPE OF FASTENING

Fixing by direct snap-fit, no tools needed

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Universal, specific Simon K45 and specific Simon 500 Cima using adaptor (ref.50012088-030)

INSTALLATION DIRECTION

Vertical according to the direction of the mechanisms

INSTALLATION TYPE

Suitable for surface and flush mounting

REGULATIONS

REGULATIONS

Directive 2014/35/UE LVD + Directive 2011/65/UE RoHS + EN 50581:2012 + EN 60669-1:1999 + EN 60669-1:1999 A1:2002 + EN 60669-1:1999 A2:2008

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING LENGTH
0

UNITARY PACKAGING VOLUME
0.3

UNITARY PACKAGING VOLUME UNIT
MMQ

UNITARY PACKAGING GROSS WEIGHT
0.01

PRODUCT NET WEIGHT
0.01

UNITARY PACKAGING WEIGHT UNIT
KGM

PACKAGING EAN
8426436047129

UNITS CONTAINED PACKAGING
10

PACKAGING HEIGHT
75

PACKAGING WIDTH
75

PACKAGING LENGTH
105

PACKAGING MEASUREMENT UNIT
MMT

PACKAGING VOLUME
0.544

PACKAGING VOLUME UNIT
MMQ

PACKAGING GROSS WEIGHT
0.96

PACKAGING NET WEIGHT
0.1

PACKAGING WEIGHT UNIT
KGM