

PD-20x20 Duo PIR+LUX SR superfacie DALI-2 Master white IP20

REF. 89212436-230



BASIC INFORMATION

DESCRIPTION

Surface presence and brightness detector PIR. The recommended installation height is 2.8 m, with a maximum height of 10 m. It has a detection angle of 360 ° and an opening angle of 180 °. The tangential detection range is 20 x 20 m and the radial detection range is 8 x 8 m.

The luminosity regulation range is 10 - 1000 lux and the timing range is 5 s - 60 min. The detector configuration is done via remote control.

It has a TEACH operating mode. Possibility of interconnection between sensors. The control protocol is DALI-2 Master. The number of dimmable luminaires via the DALI bus is 64 (2 groups).

The power supply voltage is 220 - 240 VAC. The operating temperature of the detector is: 0 - 40 °C.

White finish, IP 20 protection degree, and dimensions: 120 x 120 x 65 mm.

5-year warranty

For more product information, visit STEINEL website by clicking [here](#)

FINISH

White

COMPATIBLE WITH MECHANICAL PUSH BUTTON

Yes

ETIM CLASS

EC000133

TECHNICAL INFORMATION

FREQUENCY

50 - 60 Hz

POWER SUPPLY (V~)

220/240 V~

CONTROL

DALI2 Master

IP RATING

IP20

RAL

9010

INSTALLATION AND MAINTENANCE

MINIMUM INSTALLATION HEIGHT

2.5

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053370018

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING GROSS WEIGHT

0.38

PRODUCT NET WEIGHT

0.268

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053370018

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

161

PACKAGING WIDTH

101

PACKAGING LENGTH

143

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

2325323

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

0.38

PACKAGING NET WEIGHT

0.268

PACKAGING WEIGHT UNIT

KGM