
Trim plate for 1 quick connection connector with 3 poles male or female for 1 element white Simon K45

REF. **K18/9**



BASIC INFORMATION

DESCRIPTION

Trim plate of the series Simon K45 available in white colour and that is used for 1 connector is not included (to be purchased the plate) of connection 3-pole male or female quick of 1 element. This plate is made (according to the regulation UNE -s 60670-1: 2006) with halogen-free thermoplastic material, a material very safe that guarantees no flame spread in case of fire and low level poison in case of fire and smoke. The trim plate Simon K45 is perfect to be installed both in surface-mounted and recessed, in rooms with a temperature located between the -5 and the most of 60 ° C It measures 45 x 45 x 8.5 mm and its cleaning is very simple: You just need a soft, dry cloth and do not use any type of abrasive cleaner containing chlorine, as the plate could get damaged and not function as it should.

FINISH

White

MATERIAL

Plastic

COMPATIBILITY

Simon K45 enclosures for installation in the wall, floor, ceiling and furniture and Simon 500 Cima enclosures (need to be combined with the K45 to 500 Cima adaptor ref.50012088-030)

PACKAGING CONTENTS

Plate for one 3-pole quick connection connector

ETIM CLASS

EC000011

REMARKS

Connector not included (to be purchased separately). If using another quick connect brand, the plate is compatible with the leading manufacturers (Wieland®, Wago®, etc). To fix the connector to the plate correctly, the clips must be between 1.5 and 2 mm thick.

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

AVAILABLE IN

Versions for 1 and 2 quick-connection connectors with 3 male or female poles

MAX TEMP DURING CONSTRUCTION WORK (°C)

+60° C

FORMAT

GST18

INDICATOR FUNCTION

No

IP RATING

IP20

KIT AVAILABILITY

No

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 to 60° C

NUMBER OF MODULES

Half

RAL

9003

VERSION

Single

INSTALLATION AND MAINTENANCE

TYPE OF FASTENING

Fixing by direct snap-fit, no tools needed

INSTALLATION DIRECTION

Vertical according to the direction of the mechanisms

REMOVAL OF THE PLATE

Only with tool

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Universal, specific Simon K45 and specific Simon 500 Cima using adaptor (ref.50012088-030)

INSTALLATION TYPE

Suitable for surface and flush mounting

REGULATIONS

REGULATIONS

Directive 2014/35/UE LVD + Directive 2011/65/UE RoHS + EN 50581:2012 + EN 60535:2009 A1:2013

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING LENGTH
0

UNITARY PACKAGING VOLUME
0.3

UNITARY PACKAGING VOLUME UNIT
MMQ

UNITARY PACKAGING GROSS WEIGHT
0.009

PRODUCT NET WEIGHT
0.009

UNITARY PACKAGING WEIGHT UNIT
KGM

PACKAGING EAN
8426436036697

UNITS CONTAINED PACKAGING
20

PACKAGING HEIGHT
70

PACKAGING WIDTH
93

PACKAGING LENGTH
140

PACKAGING MEASUREMENT UNIT
MMT

PACKAGING VOLUME
911400

PACKAGING VOLUME UNIT
MMQ

PACKAGING GROSS WEIGHT
0.18

PACKAGING NET WEIGHT
0.18

PACKAGING WEIGHT UNIT
KGM