

Metal cover for metal surface mount or flush mount wall frame for 8 elements stainless steel Simon K45

REF. KMA401/8



BASIC INFORMATION

FINISH

Stainless steel

COMPATIBILITY

Simon K45 functions

ETIM CLASS

EC000007

MATERIAL

Stainless steel

PACKAGING CONTENTS

Metal cover with lock cylinder and key, screws and installation manual

REMARKS

It restricts access to connections, to prevent unwanted tampering, guaranteeing the outlet of cabling to the connected devices.

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

MAX TEMP DURING CONSTRUCTION WORK (°C)

+60° C

HEAT RESISTANCE (°C)

+125°C (according to standard IEC 60670)

IK CLASSIFICATION

10

IP RATING

IP4X

KIT AVAILABILITY

No

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 to 60° C

NUMBER OF MODULES

4 double modules

VERSION

8 elements

INSTALLATION AND MAINTENANCE

EXTINGUISHING (°C)

+850 °C / 30 seconds (GWFI in accordance with standard IEC 60695-2-11)

TYPE OF FASTENING

Using supplied screws

INSTALLATION TYPE

Suitable for installation on the flush-mounted metal wall box or on the surface-mounted metal wall box

REGULATIONS

REGULATIONS

Directive 2014/35/UE LVD + EN 60670-1:2005

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053095003

UNITARY PACKAGING WEIGHT
UNIT

KGM

PACKAGING MEASUREMENT
UNIT

MMT

UNITARY PACKAGING HEIGHT

0

PACKAGING EAN

8421053095003

PACKAGING VOLUME

2.686

UNITARY PACKAGING WIDTH

0

UNITS CONTAINED PACKAGING

1

PACKAGING VOLUME UNIT

DMQ

UNITARY PACKAGING LENGTH

0

PACKAGING HEIGHT

55

PACKAGING GROSS WEIGHT

0

UNITARY PACKAGING VOLUME

0

PACKAGING WIDTH

165

PACKAGING NET WEIGHT

0.58

UNITARY PACKAGING GROSS
WEIGHT

0.58

PACKAGING LENGTH

296

PACKAGING WEIGHT UNIT

KGM

PRODUCT NET WEIGHT

0.58