Voice and data flat plate with dust cover for 1 element and 1 RJ45 connector category 5e FTP black Simon K45

REF. **K95F/14**



BASIC INFORMATION

DESCRIPTION

In an original finishes, the plate in black voice and data flat plate with dust cover for 1 RJ45 connector of category 5e FTP, form part of our collection Simon K45 has dimensions of 45x45 mm, a thickness of 42,9 mm and is made of metal materials with halogen-free insulation self-extinguishing thermoplastic to ensure that no flame spread if it had fire, in addition to a extremely low toxicity in case of smoke. If you want to combine the voice and data plate in vertical enclosures, you must use the 90º positioner to be able to this piece in vertical position. If what you are looking for is that your home with the best solutions for workplace solutions, you can veined the collection Simon K45. A collection designed to offer the best quality and products at the forefront of technology. This comes from one of the best marks on the market.

FINISH

Black

COMPATIBILITY

Simon K45 enclosures for installation in the wall, floor, ceiling and furniture and Simon 500 Cima enclosures (need to be combined with the K45 to 500 Cima adaptor ref.50012088-038)

PACKAGING CONTENTS

Flat voice and data plate with dust cover, category 5e UTP RJ45 connector and installation manual

ETIM CLASS

EC000018

REMARKS

When combining the voice and data plate in vertical housings (mini columns, columns, Teleblock, channels, mechanism holders, etc.) you must use the 90º positioner (ref. K66) to guide the plate into a vertical position.

TECHNICAL INFORMATION

AVAILABLE MARKET
CE

CABLE SECTION ADMITTED (MM)
22-24 AWG wiring

RJ45 CONNECTION
With insertion tool

CONNECTOR CHARACTERISTICS
Category 5e FTP

RJ45 CONNECTORS
Included in voice and data plate

MAX TEMP DURING CONSTRUCTION WORK (°C)
+60° C

DUST PROTECTION
Yes

FORMAT
RJ45

IP RATING
IP20

MAINTENANCE
Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

TEMPERATURE RANGE DURING INSTALLATION (°C)
-5 to 60° C

NUMBER OF MODULES
Half

PLATE TYPE
Flat

RAL
7021

RJ45 ADAPTOR MODULE
Supplied with the voice and data plate

SNAP-FIT RJ45 PLATES
Keystone I, II, ATT®/Avaya®

SNAP-FIT TYPE
Keystone I, II, ATT®/Avaya®

VERSION
Single

INSTALLATION AND MAINTENANCE

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX
Universal, specific Simon K45 and specific Simon 500 Cima using adaptor (ref.50012088-038)

INSTALLATION DIRECTION
Vertical according to the direction of the mechanisms

INSTALLATION TYPE
Suitable for surface and flush mounting

REMOVAL OF THE PLATE
Only with tool

REGULATIONS

REGULATIONS

Directive 2011/65/UE RoHS + post. mod. | EN IEC 63000:2018 | EN 50173-1:2018*1

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING VOLUME

0.3

UNITARY PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING GROSS WEIGHT

0.031

PRODUCT NET WEIGHT

0.031

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8426436042445

UNITS CONTAINED PACKAGING

10

PACKAGING HEIGHT

65

PACKAGING WIDTH

155

PACKAGING LENGTH

210

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

2115750

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

0.65

PACKAGING NET WEIGHT

0.31

PACKAGING WEIGHT UNIT

KGM