

Downlight 709 Dip Switch On/Off Black

REF. 70921038-497



BASIC INFORMATION

DESCRIPTION

Recessed 84mm LED downlight 709 On-Off with black aluminium body and recessed design for reduced glare. Wide Flood 38° optics, tilt up to 28°, CRI>90 and CCT selector (2700K, 3000K, 4000K). Ideal for offices, hotels and retail. 79 lm/W efficiency and 30,000h lifetime.

FINISH

Black

APPLICATION

General lighting

MATERIAL

Aluminium

ETIM CLASS

EC001744

TECHNICAL INFORMATION

FREQUENCY

50 - 60 Hz

NOMINAL VOLTAGE (V~)

220/240 V~

POWER SUPPLY (V~)

220/240 V~

IP RATING

IP20

OPERATING TEMPERATURE RANGE (°C)

-10...+35

CONTROL

On/Off

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053382011

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING HEIGHT

0

PACKAGING EAN

8421053382011

PACKAGING VOLUME

1452000

UNITARY PACKAGING WIDTH

0

UNITS CONTAINED PACKAGING

1

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING LENGTH

0

PACKAGING HEIGHT

120

PACKAGING GROSS WEIGHT

0.48

UNITARY PACKAGING VOLUME

0

PACKAGING WIDTH

110

PACKAGING NET WEIGHT

0.25

UNITARY PACKAGING GROSS WEIGHT

0.48

PACKAGING LENGTH

110

PACKAGING WEIGHT UNIT

KGM

PRODUCT NET WEIGHT

0.25