

PD-24x24 PIR+LUX BT Mesh recessed box On/Off+PF white IP20

REF. 89212216-230



BASIC INFORMATION

DESCRIPTION

Presence and brightness detector for flush mounting PIR. The recommended installation height is 2.8 m, with a maximum height of 10 m. It has a detection angle of 360° and an opening angle of 160°. The tangential detection range is 24 x 24 m and the radial detection range is 9 x 9 m. The brightness regulation range is 2 - 2000 lux and the timing range is 5 s - 60 min. The detector configuration is done through potentiometers and a Bluetooth application. It has a TEACH operating mode. Possibility of interconnection between sensors via Bluetooth. It has two outputs (On/Off + Potential-free) and the maximum switchable power is 2000 W (600 W LED). The power supply voltage is 220 - 240 VAC. The operating temperature of the detector is: 0 - 40 °C. White finish, IP 20 protection rating and dimensions: 103 x 103 x 69 mm. 5-year warranty.

For more product information, visit STEINEL website by clicking [here](#)

FINISH

White

COMPATIBLE WITH MECHANICAL PUSH BUTTON

Yes

ETIM CLASS

EC000133

TECHNICAL INFORMATION

FREQUENCY

50 - 60 Hz

MAXIMUM POWER (W)

2000

RAL

9003

IP RATING

IP20

POWER SUPPLY (V~)

220/240 V~

CONTROL

2 channels (On/Off + Potential Free)

INSTALLATION AND MAINTENANCE

MINIMUM INSTALLATION HEIGHT

2.5

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053342336

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING GROSS WEIGHT

0.282

PRODUCT NET WEIGHT

0.173

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053342336

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

161

PACKAGING WIDTH

101

PACKAGING LENGTH

143

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

2325323

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

0.282

PACKAGING NET WEIGHT

0.173

PACKAGING WEIGHT UNIT

KGM