

## Intermediate push-button switch 10AX 230V~ with slender rocker and fast terminal connection system gold Simon 270

REF. 20001251-095



### BASIC INFORMATION

#### FINISH

Matt gold

#### TYPE OF ROCKER

Slender

#### MATERIAL

Thermoplastic

#### COMPATIBILITY

Simon 270 frames

#### PACKAGING CONTENTS

Mechanism, cover and instruction sheet

#### ETIM CLASS

EC001590

## TECHNICAL INFORMATION

|                                                          |                                                                                                                            |                                                      |
|----------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------|
| <b>AVAILABLE MARKET</b><br>CE                            | <b>INDICATOR FUNCTION</b><br>No                                                                                            | <b>NOMINAL VOLTAGE (V~)</b><br>230 V~                |
| <b>CABLE SECTION ADMITTED (MM)</b><br>From 1,5 to 2,5 mm | <b>CURRENT (A)</b><br>10 AX                                                                                                | <b>OPERATING TEMPERATURE RANGE (°C)</b><br>5 - 45 °C |
| <b>TYPE OF COVER</b><br>Slender                          | <b>IP RATING</b><br>IP20                                                                                                   | <b>POWER SUPPLY (V~)</b><br>230 V~                   |
| <b>NUMBER OF POSSIBLE ELEMENTS</b><br>Half element       | <b>MAINTENANCE</b><br>Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine. | <b>RAL</b><br>1036                                   |
| <b>FORMAT</b><br>Push-button                             | <b>TYPE OF MECHANISM</b><br>Pivoting                                                                                       | <b>STORAGE TEMPERATURE RANGE (°C)</b><br>-25 - 75 °C |
| <b>FREQUENCY</b><br>50 - 60 Hz                           |                                                                                                                            | <b>VOLTAGE (V~)</b><br>127/230 V~                    |

## INSTALLATION AND MAINTENANCE

|                                             |                                                             |                                                         |
|---------------------------------------------|-------------------------------------------------------------|---------------------------------------------------------|
| <b>CABLE STRIPPING NECESSARY (MM)</b><br>15 | <b>INSTALLABLE IN FLUSH MOUNT JUNCTION BOX</b><br>Universal | <b>INSTALLATION TYPE</b><br>Suitable for flush mounting |
|                                             | <b>INSTALLATION DIRECTION</b><br>Horizontal, Vertical       | <b>TYPE OF TERMINAL CONNECTION - FUNCTION 1</b><br>Fast |

## REGULATIONS

### REGULATIONS

Dir. 2014/35/UE LVD | Dir. 2011/65/UE RoHS + post. mod. | EN 60669-1:2018 | EN IEC 63000:2018

## LOGISTICS INFORMATION

### UNITARY EAN CODE

8421053269640

### UNITARY PACKAGING HEIGHT

0

### UNITARY PACKAGING WIDTH

0

### UNITARY PACKAGING LENGTH

0

### UNITARY PACKAGING MEASUREMENT UNIT

MMT

### UNITARY PACKAGING VOLUME

0

### UNITARY PACKAGING VOLUME UNIT

MMQ

### UNITARY PACKAGING GROSS WEIGHT

0.03

### PRODUCT NET WEIGHT

0.03

### UNITARY PACKAGING WEIGHT UNIT

KGM

### PACKAGING EAN

8421053269657

### UNITS CONTAINED PACKAGING

10

### PACKAGING HEIGHT

47.75

### PACKAGING WIDTH

57

### PACKAGING LENGTH

262

### PACKAGING MEASUREMENT UNIT

MMT

### PACKAGING VOLUME

713098.5

### PACKAGING VOLUME UNIT

MMQ

### PACKAGING GROSS WEIGHT

0

### PACKAGING NET WEIGHT

0.3

### PACKAGING WEIGHT UNIT

GRM

