# German socket outlet 16A 250V~ with safety device and fast terminal connection red Simon 27 Play

REF. **27432-68**



# BASIC INFORMATION

## DESCRIPTION

Base de tomada Shuko com uma intensidade de 16 A e uma potência de 250 V~ que inclui dispositivo de segurança e ligação rápida de bornes, fabricado em cor vermelho e da série Simon 27 Play. O seu tipo de funcionamento é mediante inserção e podê-lo-ás encontrar na categoria de “tomadas de corrente”. As suas dimensões são de 45x45 mm.

A base de tomada já inclui as tampas com a função de proteção infantil, para que todos os pequenos estejam protegidos perante qualquer erro elétrico na ficha. O elemento na hora da sua instalação é adequado para superfície e para encastrar o que poupa muito tempo na hora de levar a cabo a instalação.

Para mantê-lo corretamente como novo, é recomendável utilizar um pano suave e seco sem lhe acrescentar nenhum detergente abrasivo que contenha cloro ou alguma substância corrosiva. Para seu proteção é fabricado com componentes metálicos da máxima qualidade e isolantes, além disso sua embelezador é termoplástico para funcionar a máximo rendimento em diferentes intervalos de temperatura.

## FINISH

Red

## COMPATIBILITY

Simon 27 Play, Simon 27 Neos, Simon 27 Scudo, Simon 27, Simon 27 Centralisations and Simon 44 Aqua frames

## PACKAGING CONTENTS

Socket outlet with cover

## ETIM CLASS

EC000125

## REMARKS

The covers include a child-proof protective feature.

## TECHNICAL INFORMATION

### AVAILABLE MARKET
CE

### CABLE SECTION ADMITTED (MM)
2,5 mm

### NUMBER OF POSSIBLE ELEMENTS
1 element

### FORMAT
Schuko

### INDICATOR FUNCTION
No

### CURRENT (A)
16 A

### IP RATING
IP20

### MAINTENANCE
Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

### TYPE OF MECHANISM
Insertion

### MONOBLOCK
No

### NOMINAL VOLTAGE (V~)
250 V~

### OPERATING TEMPERATURE RANGE (°C)
5 - 40 °C

### STORAGE TEMPERATURE RANGE (°C)
-25 - 50 °C

### VERSION
Single

## INSTALLATION AND MAINTENANCE

### CABLE STRIPPING NECESSARY (MM)
15

### CLAW
Simon 27

### INSTALLABLE IN FLUSH MOUNT JUNCTION BOX
Universal, American and Centralisations

### INSTALLATION DIRECTION
Horizontal, Vertical

### INSTALLATION TYPE
Suitable for surface and flush mounting

### TYPE OF TERMINAL CONNECTION - FUNCTION 1
Fast

## REGULATIONS

### REGULATIONS
Dir. 2011/65/UE RoHS + post. mod. | EN IEC 63000:2018 | UNE 20315-1-1:2017 | IEC 60884-1 Ed 3.2 | UNE 20315-1-2:2017

## LOGISTICS INFORMATION

UNITARY EAN CODE
8421053252109

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING LENGTH
0

UNITARY PACKAGING MEASUREMENT UNIT
MMT

UNITARY PACKAGING VOLUME
0

UNITARY PACKAGING VOLUME UNIT
MMQ

UNITARY PACKAGING GROSS WEIGHT
0.052

PRODUCT NET WEIGHT
0.052

UNITARY PACKAGING WEIGHT UNIT
KGM

PACKAGING EAN
8421053051535

UNITS CONTAINED PACKAGING
10

PACKAGING HEIGHT
53

PACKAGING WIDTH
105

PACKAGING LENGTH
221

PACKAGING MEASUREMENT UNIT
MMT

PACKAGING VOLUME
1229865

PACKAGING VOLUME UNIT
MMQ

PACKAGING GROSS WEIGHT
0.52

PACKAGING NET WEIGHT
0.52

PACKAGING WEIGHT UNIT
KGM