

Industrial luminaire 816.40 NW Intensive DALI

REF. 81640338-384



BASIC INFORMATION

DESCRIPTION

The home Simon, always at the forefront of research for lighting and troubleshooting for workers presents its new line 816 of industrial lateral luminaires. Industrial luminaire 816.40 NW intensive. DALI. 11500 lm / 90W. Luminaire suspended for industrial lighting of. Black finish. The neutral colour temperature. Diameter 360 mm, height of suspended 490 mm Of optics. The tab photometric indicates that distributes the light beam at an angle of 30 °, sending it so SPHERE down to be lit areas very specific way of. Suspended system using string is not included. The IP68 connectors are included. System of switching on On -off or DALI according to needs. DALI is a communications interface digital, and addressable for lighting systems. This system is an international standard, in accordance with the IEC 62386, which ensures the compatibility and interchangeability of equipment from different manufacturers. The material is aluminium and Poli carbonate, and is be lit of the security fotobiológica. Its weight is 3.6 kg its service life is 30,000 HS. Guarantees functionality and attractive design, when connected to its capacity of lighting on the work areas specific, high durability and maintenance of the light flux light during hours without the flashes that normally make another type of lighting systems that are not LED.

APPLICATION

General lighting,Intensive lighting

PACKAGING CONTENTS

1 unit

ETIM CLASS

EC001716

TECHNICAL INFORMATION

FREQUENCY

50 - 60 Hz

CRI

80

LUMENS (LM)

11500 lm

IK CLASSIFICATION

08

DRIVER INCLUDED

Yes

LUMENS/W

11500 lm/90W

IP RATING

IP65

ELECTRICAL CLASS

Type 1

OPTICS

Intensive

OPERATING TEMPERATURE RANGE (°C)

-15 - 40 °C

INTEGRATED POWER SUPPLY

Yes

PHOTOBIOLOGICAL CLASSIFICATION

Exempt category

POWER SUPPLY (V~)

100/240 V~

L70 (°C)

50,000 h at 25 °C

POWER (W)

90 W

COLOR TEMPERATURE (K)

4000 K

COLOR TYPE

NW

SERVICE LIFE

50.000 h

CONTROL

DALI

LIGHTING EFFICIENCY (LM/W)

128 lm/W

CHROMATICS CRI ICONS

CRI
80

INSTALLATION AND MAINTENANCE

INSTALLATION TYPE

Suspended

TYPE OF TERMINAL CONNECTION - FUNCTION 1

Screw

REGULATIONS

WARRANTY

5 years 50,000 h

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053194560

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING GROSS WEIGHT

5.9

PRODUCT NET WEIGHT

4.8

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053194560

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

190

PACKAGING WIDTH

420

PACKAGING LENGTH

420

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

33516000

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

5.9

PACKAGING NET WEIGHT

4.8

PACKAGING WEIGHT UNIT

KGM