

Modular luminaire 720 Advance M4 60x60 Low Glare WW

REF. 72060040-683



BASIC INFORMATION

DESCRIPTION

With micro prismatic optics and a warm hue of light (WW) temperature of 3000 K, the luminaire 720 modular Advance M4 60 x 60 of the collection Simon for indoor lighting, to reinvent the mechanisms of lighting with the most high efficiency. System with anti glare LowGlare, has 3200 lumens / 28 W. Compatible with power Volt voltage 100-240 and frequency of 50-60 Hz, it can reach a maximum temperature of 40 °C. The luminaire modular Advance, providing a reduction in energy consumption of up to 20%, with a maintenance of the light flux of light 40,000 hours at 25 ° C and L90, for of 100,000 hours for the L70. Designed for installation in false ceiling on hardware, has a dimension of 595 x 595 mm and includes control system, switching on ON-OFF.

DIFFUSER MATERIAL

PMMA

PACKAGING CONTENTS

1 unit

APPLICATION

General lighting

ETIM CLASS

EC002892

TECHNICAL INFORMATION

FREQUENCY

50 - 60 Hz

DRIVER INCLUDED

Yes

LIGHTING EFFICIENCY (LM/W)

114 lm/W

IP RATING

IP44

ELECTRICAL CLASS

Tipo 2

LUMENS (LM)

3200 lm

OPERATING TEMPERATURE RANGE (°C)

40 °C maximum

INTEGRATED POWER SUPPLY

Yes

LUMENS/W

3200 lm/28W

POWER SUPPLY (V~)

100/240 V~

L70 (°C)

100,000 h at 25 °C

OPTICS

Microprismatic

COLOR TEMPERATURE (K)

3000 K

L90 (°C)

40,000 h at 25 °C

PHOTOBIOLOGICAL CLASSIFICATION

Exempted category

CONTROL

On/Off

LIGHT BEAM APERTURE ANGLE (°)

120°

POWER (W)

28 W

CRI

82

COLOR TYPE

WW

SERVICE LIFE

50.000 h

CHROMATICS CRI ICONS

CRI
82

INSTALLATION AND MAINTENANCE

INSTALLATION ALTERNATIVES

Plaster ceiling, surface mount, concealed or semi-concealed profile.

MINIMUM INSTALLATION HEIGHT

120

INSTALLATION TYPE

False ceiling, visible hardware

TYPE OF TERMINAL

CONNECTION - FUNCTION 1

Quick connector

REGULATIONS

WARRANTY

5 years 50,000 h

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053191712

UNITARY PACKAGING WEIGHT
UNIT

KGM

PACKAGING MEASUREMENT
UNIT

MMT

UNITARY PACKAGING HEIGHT

0

PACKAGING EAN

8421053191712

PACKAGING VOLUME

0.234

UNITARY PACKAGING WIDTH

0

UNITS CONTAINED PACKAGING

1

PACKAGING VOLUME UNIT

HLT

UNITARY PACKAGING LENGTH

0

PACKAGING HEIGHT

65

PACKAGING GROSS WEIGHT

0

UNITARY PACKAGING VOLUME

0

PACKAGING WIDTH

600

PACKAGING NET WEIGHT

5

UNITARY PACKAGING GROSS
WEIGHT

5.58

PACKAGING LENGTH

600

PACKAGING WEIGHT UNIT

KGM

PRODUCT NET WEIGHT

5