

PD-4x4 Slim PIR+LUX SR recessed box On/Off white IP20

REF. 89219110-230



BASIC INFORMATION

DESCRIPTION

Presence and brightness detector for flush mounting PIR. The recommended installation height is 2.8 m, with a maximum height of 4 m. It has a detection angle of 360° and an opening angle of 71°. The tangential detection range is 4 x 4 m and the radial detection range is 4 x 4 m. The luminosity regulation range is 10 - 1000 lux and the timing range is 1 min - 15 min. The configuration of the detector is done via remote control. It features a TEACH operating mode. Possibility of interconnection between master/master sensors and master/slave up to 10 detectors. The control output is On/Off and the maximum switchable power is 1000 W (64 LED). The power supply voltage is 220 - 240 VAC. The operating temperature of the detector is: 0 - 40 °C. White finish, IP 20 protection rating and dimensions: 80 x 80 x 50 mm. 5-year warranty.

For more product information, visit STEINEL website by clicking [here](#)

FINISH

White

COMPATIBLE WITH MECHANICAL PUSH BUTTON

Yes

ETIM CLASS

EC000133

TECHNICAL INFORMATION

FREQUENCY

50 - 60 Hz

MAXIMUM POWER (W)

1000

RAL

9010

IP RATING

IP20

POWER SUPPLY (V~)

220/240 V~

CONTROL

On/Off

INSTALLATION AND MAINTENANCE

MINIMUM INSTALLATION HEIGHT

2.5

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053343111

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING GROSS WEIGHT

0.15

PRODUCT NET WEIGHT

0.078

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053343111

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

130

PACKAGING WIDTH

90

PACKAGING LENGTH

90

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

1053000

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

0.15

PACKAGING NET WEIGHT

0.078

PACKAGING WEIGHT UNIT

KGM