

## On-desk set with 4 German socket outlets aluminium Simon 400

REF. 42404000-133



### BASIC INFORMATION

#### DESCRIPTION

If you are looking for a connection for 4 elements that this fitted to the furniture, thus avoiding the use of uncomfortable alargadores. Simon offers you this kit of desk top complete with 4 socket-outlets plug with aluminium finish and made of metal of the prestigious series Simon 400. A perfect solution that combines design, durability and security fire-fighting. The extra resistance that has this piece is achieved thanks to the profile of anodised aluminium, a material very durable is the knocks. As a measure effective to prevent the propagation of the flame in case of fire, Simon manufactures the covers and fastenings of this series with self-extinguishing thermoplastic. Connections for 250 volts with a current of 16 amps. This kit avant-garde measures 205 x 120 x 80 millimetres and to complete its installation, it must be combined with the Simon 400.

#### FINISH

Aluminium

#### MATERIAL

Metal

#### COMPATIBILITY

Can be combined with the range of Electric Cabling from Simon.

#### PACKAGING CONTENTS

Pre-wired profile, table-top supports, rear trim cover and installation manual.

## TECHNICAL INFORMATION

### AVAILABLE MARKET

CE

### INSULATION RESISTANCE (V-MΩ)

>5 MΩ at 500 V

### NOMINAL VOLTAGE (V~)

250 V~

### DIELECTRIC STRENGTH

No holes or contours, with 2000V at 50 Hz for 1 minute

### CURRENT (A)

16 A

### TYPE OF POWER SUPPLY CONNECTOR

Wieland  GST 18i male 3-pole overhead connector with 22 cm patch cord

### MAX TEMP DURING CONSTRUCTION WORK (°C)

+60  C

### IP RATING

IP30

### MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

### RAL

9006

### FORMAT

Schuko

### NUMBER OF SOCKETS

4 sockets for standard current circuit

### HEAT RESISTANCE (°C)

+70°C (according to standard IEC 60670)

### TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 at +60  C

### VERSION

4 elements

## INSTALLATION AND MAINTENANCE

### CLAW RANGE OF OPERATION (MM)

Between 16 and 40 mm

### TYPE OF FASTENING

By tightening existing clamps in the fastening bracket.

### SECURING POSSIBILITIES

Using clips included in the fastening brackets

### EXTINGUISHING (°C)

+70 °C (according to standard IEC 60670)

### INSTALLATION TYPE

Suitable for fixing to furniture.

### MOUNTING WITHOUT ACCESSORIES

Supplied with all necessary materials for installation.

## REGULATIONS

### REGULATIONS

Directiva 2014/35/UE LVD;Directiva 2011/65/UE RoHS;EN 50581:2012;EN 60670-1:2005;EN 60670-1:2005 A1:2013;IEC 60884-1 Ed 3.2;

## LOGISTICS INFORMATION

### UNITARY EAN CODE

8421053195727

### UNITARY PACKAGING HEIGHT

0

### UNITARY PACKAGING WIDTH

0

### UNITARY PACKAGING LENGTH

0

### UNITARY PACKAGING VOLUME

0

### UNITARY PACKAGING GROSS WEIGHT

0.8

### PRODUCT NET WEIGHT

0.8

### UNITARY PACKAGING WEIGHT UNIT

KGM

### PACKAGING EAN

8421053195727

### UNITS CONTAINED PACKAGING

1

### PACKAGING HEIGHT

240

### PACKAGING WIDTH

125

### PACKAGING LENGTH

95

### PACKAGING MEASUREMENT UNIT

MMT

### PACKAGING VOLUME

2850000

### PACKAGING VOLUME UNIT

MMQ

### PACKAGING GROSS WEIGHT

0

### PACKAGING NET WEIGHT

0.8

### PACKAGING WEIGHT UNIT

KGM