

2-way rotary dimmer switch for half element 40 to 500W/VA white Simon 27 Play

REF. 27313-34



BASIC INFORMATION

DESCRIPTION

Each activity requires a specific light intensity. The excess or lack of lighting can cause problems when carrying out different tasks in our home or work. - thanks to this regulator 2-way switch half element rotary light from 40 to 500 W / VA of the Simon 27 Play series, this will never be a problem. Its value for money is unrivalled in the market regulator. This is a universal electronic narrow-module voltage available in white colour. Its ease of use, with a rotary type of operation, is another of its advantages, besides being suitable for surface and flush mounting. For its maintenance, it is only necessary to a soft cloth slightly moistened in soapy water, like the rest of our products, the quality of their materials is excellent with electronic components with halogen-free insulation and thermoplastic trim.

FINISH

White

COMPATIBLE WITH 230V INCANDESCENT AND HALOGEN LAMPS (W)

500 VA

PACKAGING CONTENTS

Dimmer and instruction sheet

COMPATIBILITY

Simon 27 Play, Simon 27 Neos,
Simon 27 Scudo, Simon 27,
Simon 27 Centralisations and
Simon 44 Aqua frames

COMPATIBLE WITH MECHANICAL PUSH BUTTON

No

ETIM CLASS

EC000025

COMPATIBLE WITH MECHANICAL 2-WAY/CROSSOVER SWITCH

Yes

COMPATIBLE WITH MECHANICAL SWITCH

No

REMARKS

Two main electronic voltage regulators cannot be connected in the same circuit.

TECHNICAL INFORMATION

AVAILABLE MARKET CE	COMPATIBLE WITH FLUORESCENT LAMPS WITH 1- 10V DIMMABLE ELECTRONIC BALLAST	TYPE OF MECHANISM Rotary
CABLE SECTION ADMITTED (MM) From 1,5 to 2,5 mm	No	MINIMUM POWER (W) 40
NUMBER OF CONTACTS 3	COMPATIBLE WITH FLUORESCENT LAMPS (VA) No	COMPATIBLE WITH MOTORS (VA) No
NUMBER OF CONTROLLABLE CIRCUITS 1	INDICATOR FUNCTION Yes	OPERATING TEMPERATURE RANGE (°C) 0 - 40 °C
COMPATIBLE WITH HALOGENS WITH ELECTROMAGNETIC TRANSFORMER (W) 500 VA	IP RATING IP20	POWER SUPPLY (V~) 230 V~
COMPATIBLE WITH ELECTRONIC AUXILIARY No	COMPATIBLE WITH LOW CONSUMPTION (W) No	STORAGE TEMPERATURE RANGE (°C) -20 - 75 °C
COMPATIBLE WITH HALOGENS WITH ELECTRONIC TRANSFORMER (W) 300 VA	MAINTENANCE Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.	TYPE 2-way dimmer switch
NUMBER OF POSSIBLE ELEMENTS Half element	MAXIMUM POWER (W) 500	VERSION Single
	MAXIMUM QUANTITY PER CIRCUIT 1	NUMBER OF WIRES 2

INSTALLATION AND MAINTENANCE

CABLE STRIPPING NECESSARY (MM) 8	INSTALLABLE IN FLUSH MOUNT JUNCTION BOX Universal, American and Centralisations	INSTALLATION TYPE Suitable for surface and flush mounting
--	--	---

REGULATIONS

REGULATIONS

Dir. 2014/35/UE LVD | Dir. 2014/30/UE EMC | Dir. 2011/65/UE RoHS + post. mod. | EN 60669-2-1:2004 | EN 60669-2-1:2004 A1:2009 | EN 60669-2-1:2004 A12:2010 | EN IEC 63000:2018

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053060148

PRODUCT NET WEIGHT

0.02

PACKAGING MEASUREMENT

UNIT

MMT

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WEIGHT

UNIT

KGM

PACKAGING VOLUME

110.124

UNITARY PACKAGING WIDTH

0

PACKAGING EAN

8421053060148

PACKAGING VOLUME UNIT

CMQ

UNITARY PACKAGING LENGTH

0

UNITS CONTAINED PACKAGING

1

PACKAGING GROSS WEIGHT

0.05

UNITARY PACKAGING VOLUME

0

PACKAGING HEIGHT

23

PACKAGING NET WEIGHT

0.02

UNITARY PACKAGING VOLUME UNIT

MMQ

PACKAGING WIDTH

57

PACKAGING WEIGHT UNIT

KGM

UNITARY PACKAGING GROSS WEIGHT

0.02

PACKAGING LENGTH

84