

Adjustable floor box for 2 elements in concrete floor installation graphite Simon 500 Cima

REF. 52050001-038



BASIC INFORMATION

DESCRIPTION

Adjustable floor box for installation in concrete for two elements and finishes in Graphite within the Simon 500 Cima collection. The adjustable floor box Simon 500 Cima, fitting to the needs of each room to be suitable for installation both in concrete floor and raised floor because it allows you to regulate the depth of 70 to 100 mm in a concrete floor, and 90 to 120 mm if it is raised floor .It is manufactured with halogen-free thermoplastic materials,, preventing the spread of flames in the event of fire, and can reach a maximum temperature of 90 °C. For its installation, it must be combined with a plastic tray (ref.52052101-035). With its size of 132 x 187 x 76 mm and its finishes in Graphite, the floor box of the collection Simon 500 Cima, is synonymous with quality, elegance and innovation, suitable for any type of home, living room or office.

FINISH

Graphite

MATERIAL

Plastic

COMPATIBILITY

Simon 500 Cima and Simon 27 Play/Simon K45 mechanisms (using a specific adaptor)

PACKAGING CONTENTS

Floor box, metal partition wall, ground connection cable, screws and installation manual

ETIM CLASS

EC000024

REMARKS

To complete the installation of the product, once configured, it must be combined with a plastic tray (ref.52052101-035). Alternatively, it may be combined with flush-mount trim cover (ref.52053101-038) in cases where the same floor lining is not installed.

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

PROTECTION AGAINST DIRECT ACCESS OF CONTACTS

No

PROTECTION AGAINST ENTRY OF DUST AND SMALL OBJECTS

Yes, thanks to the inclusion of protective foam

AVAILABLE IN

2, 4, 6, 8 and 12 elements

NUMBER OF CLAMP-HOLDER HOLES

2

DIELECTRIC STRENGTH

No holes or contours, with 2000V at 50 Hz for 1 minute

MAX TEMP DURING CONSTRUCTION WORK (°C)

+90 °C

ELECTROMAGNETIC IMMUNITY FOR VDM WIRING

Secured by installing the metal partition wall in the housings fitted into the box for this purpose.

HEAT RESISTANCE (°C)

+125°C (according rule IEC 60695-10-2)

IK CLASSIFICATION

08

INSULATION RESISTANCE (V-MΩ)

>5 MOhms at 500V

IP RATING

IP4X

KIT AVAILABILITY

No

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

MAXIMUM LOAD (KG)

800kg

TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 to 60 °C

NUMBER OF MODULES

2 modules

RAL

7021

RECESS DIMENSION (MM)

170 x 115 mm

NUMBER OF SIDE ENTRANCES

6

VERSION

2 elements

INSTALLATION AND MAINTENANCE

CLAW RANGE OF OPERATION (MM)

Between 14 and 54 mm

REMOVAL OF COMPONENTS

Only with tool

NUMBER OF COVER OPENING POSITIONS

2

EXTINGUISHING (°C)

+850 °C / 30 seconds (GWFI in accordance with standard IEC 60695-2-11)

TYPE OF FASTENING

Using fastening claws on the concrete tray (supplied with the floor box)

REMOVAL OF THE FRAME

Only with tool

CAN BE INSTALLED IN TRAY

Plástica

INSTALLATION DIRECTION

Horizontal, Vertical

INSTALLATION TYPE

Especially designed to be installed in concrete floors, although it is also suitable for installation in raised floors

REGULATIONS

REGULATIONS

Directive 2014/35/UE LVD + EN 60670-23:2008

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053092682

UNITARY PACKAGING WEIGHT
UNIT

KGM

PACKAGING MEASUREMENT
UNIT

MMT

UNITARY PACKAGING HEIGHT

0

PACKAGING EAN

8421053092682

PACKAGING VOLUME

2.871

UNITARY PACKAGING WIDTH

0

UNITS CONTAINED PACKAGING

1

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING LENGTH

0

PACKAGING HEIGHT

95

PACKAGING GROSS WEIGHT

0

UNITARY PACKAGING VOLUME

0

PACKAGING WIDTH

155

PACKAGING NET WEIGHT

0.6

UNITARY PACKAGING GROSS
WEIGHT

0.6

PACKAGING LENGTH

195

PACKAGING WEIGHT UNIT

KGM

PRODUCT NET WEIGHT

0.6

