

Luminaire HOLE 50 Pro Flush mount 3000K Flood Yellow CRI90

REF. 91411962-301



BASIC INFORMATION

FINISH

Yellow

APPLICATION

Flush mount

PACKAGING CONTENTS

1 unit

TECHNICAL INFORMATION

FREQUENCY

50 - 60 Hz

CRI

90

LUMENS (LM)

1600 lm

IP RATING

IP20

DRIVER INCLUDED

No

LUMENS/W

1600

OPERATING TEMPERATURE RANGE (°C)

0 - 35 °C

ELECTRICAL CLASS

Type 3

MACADAM STEPS

<3 Step MacAdam

POWER SUPPLY (V~)

34 V~

L70 (°C)

150.000h at 25°C

OPTICS

Flood 35°

COLOR TEMPERATURE (K)

3000 K

L90 (°C)

40.000h at 25°C

POWER (W)

20 W

LIGHTING EFFICIENCY (LM/W)

103 lm/W

SERVICE LIFE

50.000 h

INSTALLATION AND MAINTENANCE

INSTALLATION TYPE

Flush mount

REGULATIONS

EAC MARKED

Yes

WARRANTY

5 years

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WEIGHT
UNIT
KGM

PACKAGING MEASUREMENT
UNIT
MMT

UNITARY PACKAGING WIDTH
0

PACKAGING EAN
8436547055821

PACKAGING VOLUME
4083200

UNITARY PACKAGING LENGTH
0

UNITS CONTAINED PACKAGING
1

PACKAGING VOLUME UNIT
MMQ

UNITARY PACKAGING VOLUME
0

PACKAGING HEIGHT
80

PACKAGING GROSS WEIGHT
0.432

UNITARY PACKAGING GROSS
WEIGHT
0

PACKAGING WIDTH
176

PACKAGING NET WEIGHT
0.432

PRODUCT NET WEIGHT
0.432

PACKAGING LENGTH
290

PACKAGING WEIGHT UNIT
KGM