

Wall movement and brightness detector On/Off BL 180° 5m black

REF. 89202140-638



BASIC INFORMATION

DESCRIPTION

Wall-mounted motion and light detector HF. The recommended installation height is 1.8 m, with a maximum height of 2 m. It has a detection angle of 160° and an opening angle of 100°. The tangential detection range is 5 m and the radial detection range is 5 m. The light regulation range is 2 - 2000 lux and the timing range is 5 s - 60 min. The detector configuration is done via potentiometers and Bluetooth application. It features a TEACH operating mode. Possibility of interconnection between sensors via Bluetooth. The control output is On/Off and the maximum switchable power is 2000 W. The power supply voltage is 220 - 240 VAC. The operating temperature of the detector is: -20 - 50 °C. Black finish, IP 54 protection degree and dimensions: 118 x 120 x 120 mm. 5-year warranty.

For more product information, visit STEINEL website by clicking [here](#)

FINISH

Black

COMPATIBILITY

Simon Sensor Pro

COMPATIBLE WITH MECHANICAL PUSH BUTTON

No

TECHNICAL INFORMATION

FREQUENCY

50 - 60 Hz

MAXIMUM POWER (W)

2000

RAL

9005

IP RATING

IP54

POWER SUPPLY (V~)

220/240 V~

CONTROL

On/Off

INSTALLATION AND MAINTENANCE

MINIMUM INSTALLATION HEIGHT

1.8

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053357613

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING GROSS WEIGHT

0.55

PRODUCT NET WEIGHT

0.36

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053357613

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

160

PACKAGING WIDTH

115

PACKAGING LENGTH

205

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

2325323

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

0.55

PACKAGING NET WEIGHT

0.36

PACKAGING WEIGHT UNIT

KGM