

Modular Luminaire 720 Advance M4 60x60 WW

REF. 72060040-883



BASIC INFORMATION

DESCRIPTION

Simon has created the line of general lighting 720. Through these high efficiency luminaires for general lighting, you have at your fingertips a product not only offers you solutions for installation quick and easy to maintain, but also the guarantee of the return on investment in the short term. This is possible thanks to its high light output (+ of 100 lm / W). Also because there is a reduction in energy consumption unit up to 20% compared to conventional luminaire, with electronic ballast. This, without dudarlo, guarantees maximum energy savings by reducing light points up to 50%, which maintains the lighting levels in the work plane. This is of a device of indoor lighting, range Luminaire 720 modular Advance M4, Square of 60x60. Colour temperature 300 k WW. Category B 720 modular Luminaires. Translucent. To 40,000 h at 25 ° C. 100-240 V50 / 60 Hz. Switching on ON-OFF. Supports up to 40°C maximum. Weight 4.9 kg Colour White. For installation in false ceiling, flat or sloped, or in hardware 595x595x60 mm dimensions.

DIFFUSER MATERIAL

PMMA

PACKAGING CONTENTS

1 unit

APPLICATION

General lighting

ETIM CLASS

EC002892

TECHNICAL INFORMATION

FREQUENCY

50 - 60 Hz

DRIVER INCLUDED

Yes

LIGHTING EFFICIENCY (LM/W)

129 lm/W

IP RATING

IP44

ELECTRICAL CLASS

Tipo 2

LUMENS (LM)

3600 lm

OPERATING TEMPERATURE RANGE (°C)

40 °C maximum

INTEGRATED POWER SUPPLY

Yes

LUMENS/W

3600 lm/28W

POWER SUPPLY (V~)

100/240 V~

L70 (°C)

100,000 h at 25 °C

OPTICS

Translucent

COLOR TEMPERATURE (K)

3000 K

L90 (°C)

40,000 h at 25 °C

PHOTOBIOLOGICAL CLASSIFICATION

Exempted category

CONTROL

On/Off

LIGHT BEAM APERTURE ANGLE (°)

120°

POWER (W)

28 W

CRI

82

COLOR TYPE

WW

SERVICE LIFE

50.000 h

CHROMATICS CRI ICONS

CRI
82

INSTALLATION AND MAINTENANCE

INSTALLATION ALTERNATIVES

Plaster ceiling, surface mount, concealed or semi-concealed profile.

MINIMUM INSTALLATION HEIGHT

120

INSTALLATION TYPE

False ceiling, visible hardware

TYPE OF TERMINAL

CONNECTION - FUNCTION 1

Screw

REGULATIONS

WARRANTY

5 years 50,000 h

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053124635

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING GROSS WEIGHT

5.58

PRODUCT NET WEIGHT

5

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053124635

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

65

PACKAGING WIDTH

600

PACKAGING LENGTH

600

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

0.234

PACKAGING VOLUME UNIT

HLT

PACKAGING GROSS WEIGHT

5.58

PACKAGING NET WEIGHT

5

PACKAGING WEIGHT UNIT

KGM