


Aluminium mini column with 1-side for 6 elements Simon K45

REF. ALK116/8



BASIC INFORMATION

DESCRIPTION

Maximum workplace solutions in a small space thanks to the Simon K45 mini column Aluminium. This 1 side and mini column for 6 elements is suitable for installing on any floor type, whether raised or concrete. With the possibility of having the electrical cabling flush-mounted in concrete or raised floor, Simon K45 offers you the possibility to adapt mini column to the floor trunking distribution baseboard to take advantage of the distribution of cabling and have functions of workplace solutions, voice, data and multimedia connections. With dimensions of 315 x 70 x60 mm, made up of Aluminium and with its metallic finishes, the K45 mini column is elegance and discretion capable of adapting to any type of espacio. Esta mini column is synonymous with functionality, innovation and workplace solutions in the entire range Simon K45 providing to its work area connections effective in a reduced space.

FINISH

Metal

COMPATIBILITY

Simon K45 functions

ETIM CLASS

EC001941

MATERIAL

Aluminium

PACKAGING CONTENTS

Mini column, floor attachment base, front cover, upper trim, screws and installation manual

REMARKS

Possibility to adapt the K45 mini column to the floor trunking distribution baseboard to take advantage of the cable routing on the floor and to make use of the electrical, voice, data and multimedia connectivity.

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

AVAILABLE IN

1-sided, 2-sided (oval) and 4-sided

DIELECTRIC STRENGTH

Without perforation or contournement with 2000 V at 50H during 1 minute

MAX TEMP DURING CONSTRUCTION WORK (°C)

+120° C

EARTHING RESISTANCE

< 0.05 ?

ELECTRICAL PROPERTIES

With electrical continuity

HEAT RESISTANCE (°C)

+650°C (according rule IEC 60695-10-2)

INSULATION RESISTANCE (V-MΩ)

5 MOhms at 500 V.

IP RATING

IP4X

KIT AVAILABILITY

No

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

TEMPERATURE RANGE DURING INSTALLATION (°C)

-25 a 120° C

NUMBER OF MODULES

6 wide modules

VERSION

1-sided

INSTALLATION AND MAINTENANCE

REMOVAL OF COMPONENTS

Only with tool

REMOVAL OF COVER

Only with tool

TYPE OF FASTENING

Using supplied screws

INSTALLATION DIRECTION

Vertical

INSTALLATION TYPE

Suitable for installing on any floor type, whether raised or concrete

SCREWS REQUIRED FOR FLOOR FIXING

4

REGULATIONS

REGULATIONS

Directive 2014/35/UE LVD + EN 50085-2-4:2009

LOGISTICS INFORMATION

UNITARY EAN CODE

8426436033252

PRODUCT NET WEIGHT

0.755

PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING VOLUME

6854400

UNITARY PACKAGING WIDTH

0

PACKAGING EAN

8426436033252

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING LENGTH

0

UNITS CONTAINED PACKAGING

1

PACKAGING GROSS WEIGHT

0.841

UNITARY PACKAGING VOLUME

0.3

PACKAGING HEIGHT

102

PACKAGING NET WEIGHT

0.755

UNITARY PACKAGING VOLUME UNIT

MMQ

PACKAGING WIDTH

140

PACKAGING WEIGHT UNIT

KGM

UNITARY PACKAGING GROSS WEIGHT

0.755

PACKAGING LENGTH

480