Voice and data flat plate for 1 element without dust cover for 1 Nexans® RJ45 connector black Simon K45

REF. **K085/14**



BASIC INFORMATION

DESCRIPTION

The plate of voice and data plate without dust cover with 1 element for 1 and 2 RJ45 Nexans ® part of the series Simon K45. This piece, suitable for surface or flush mounting, measuring 45x45 mm and a thickness of 8.5 mm and a stylish finished in black. Also, thanks to its composition with halogen-free thermoplastic materials, it guarantees that the flame spread notional is not in the event of a fire, and low toxicity if had smoke. If you want to combine the voice and data plate in vertical enclosures – as mini columns, columns, Teleblock, channels, mechanism holders _ x0085 _ – it is necessary to use the 90º positioner to be able to guide the plate into a vertical position. This collection Simon K45 presents the best solutions of workplace solutions for those who are looking for that your home has all the amenities on the market. And all, thanks to the commitment of a brand like Simon by always offer the latest market innovations.

FINISH

Black

COMPATIBILITY

Simon K45 enclosures for installation in the wall, floor, ceiling and furniture and Simon 500 Cima enclosures (need to be combined with the K45 to 500 Cima adaptor ref.50012088-038)

PACKAGING CONTENTS

Flat voice and data plate without dust cover

ETIM CLASS

EC000018

REMARKS

When combining the voice and data plate in vertical housings (mini columns, columns, Teleblock, channels, mechanism holders, etc.) you must use the 90º positioner (ref. K66) to guide the plate into a vertical position.

TECHNICAL INFORMATION

AVAILABLE MARKET
CE

COMPATIBLE WITH CONNECTORS
Nexans® LANmark®-5 EVO, LANmark®-6 EVO.

RJ45 CONNECTORS
Not included in voice and data plate

MAX TEMP DURING CONSTRUCTION WORK (°C)
+60° C

DUST PROTECTION
No

FORMAT
RJ45

IP RATING
IP20

MAINTENANCE
Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

TEMPERATURE RANGE DURING INSTALLATION (°C)
-5 to 60° C

NUMBER OF MODULES
Half

PLATE TYPE
Flat

RAL
7021

RJ45 ADAPTOR MODULE
Included in voice and data plate

SNAP-FIT RJ45 PLATES
Nexans® RJ45 connectors

SNAP-FIT TYPE
Nexans® RJ45 connectors

VERSION
Single

INSTALLATION AND MAINTENANCE

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX
Universal, specific Simon K45 and specific Simon 500 Cima using adaptor (ref.50012088-038)

INSTALLATION DIRECTION
Vertical according to the direction of the mechanisms

INSTALLATION TYPE
Suitable for surface and flush mounting

REMOVAL OF THE PLATE
Only with tool

REGULATIONS

REGULATIONS
Directive 2011/65/UE RoHS + post. mod. | EN IEC 63000:2018 | EN 50173-1:2018*1

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING LENGTH
0

UNITARY PACKAGING VOLUME
0.3

UNITARY PACKAGING VOLUME UNIT
MMQ

UNITARY PACKAGING GROSS WEIGHT
0.011

PRODUCT NET WEIGHT
0.011

UNITARY PACKAGING WEIGHT UNIT
KGM

PACKAGING EAN
8426436037229

UNITS CONTAINED PACKAGING
20

PACKAGING HEIGHT
70

PACKAGING WIDTH
93

PACKAGING LENGTH
140

PACKAGING MEASUREMENT UNIT
MMT

PACKAGING VOLUME
911400

PACKAGING VOLUME UNIT
MMQ

PACKAGING GROSS WEIGHT
0.22

PACKAGING NET WEIGHT
0.22

PACKAGING WEIGHT UNIT
KGM