

Customisable on-desk set with 2 German socket outlets and 3 empty elements aluminium Simon 400

REF. 42502000-133



BASIC INFORMATION

DESCRIPTION

Optimise the space of your work area and unified its devices connected in a single mechanism, with the kit of desk top customizable of Simon 400. With a design of clean lines and aluminium finishes, it consists of 2 Schuko socket outlets and 3 elements unreachable to choose the specific function that requires the space. Compatible with a voltage of power of 250 Volts, and 16 Ampere current, is connected to figure Wieland and has a dielectric strength, with no holes or contours, 2000 V at 50H per minute, and a insulation resistance > 5 M Ω at 500 V. Its compact design, together with its flush installation in furniture with manual elevation, ensure that the set occupied by the minimum space to be able to a greater amplitude and functionality in its working area. Innovation, functionality and design adapted to the needs of each environment with Simon 400.

FINISH

Aluminium

MATERIAL

Metal

COMPATIBILITY

Functions of the Simon 400 range, combinable with the Simon Electric Cabling range.

PACKAGING CONTENTS

Pre-wired profile, table-top supports, rear trim cover and installation manual.

ETIM CLASS

EC002759

REMARKS

To complete the product installation combine it with the Simon 400 functions (refs. 400XXXXX-03X).

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

DIELECTRIC STRENGTH

No holes or contours, with 2000V at 50 Hz for 1 minute

MAX TEMP DURING CONSTRUCTION WORK (°C)

+60  C

NUMBER OF POSSIBLE ELEMENTS

3

FORMAT

Schuko

HEAT RESISTANCE (°C)

+70°C (according to standard IEC 60670)

INSULATION RESISTANCE (V-MΩ)

>5 MΩ at 500 V

CURRENT (A)

16 A

IP RATING

IP30

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 at +60  C

TYPE OF POWER SUPPLY CONNECTOR

Wieland  GST 18i male 3-pole overhead connector with 22 cm patch cord

RAL

9006

NUMBER OF REAR ENTRANCES

3

NUMBER OF SOCKETS

2 sockets for standard current circuit

VERSION

5 elements

VOLTAGE (V~)

250 V~

INSTALLATION AND MAINTENANCE

CLAW RANGE OF OPERATION (MM)

Between 16 and 40 mm

REMOVAL OF COMPONENTS

EXTINGUISHING (°C)

+70 °C (according to standard IEC 60670)

TYPE OF FASTENING

By tightening existing clamps in the fastening bracket.

INSTALLATION TYPE

Suitable for fixing to furniture.

REMOVAL OF THE PLATE

Only with tool

SECURING POSSIBILITIES

Using clips included in the fastening brackets

MOUNTING WITHOUT ACCESSORIES

Supplied with all necessary materials for installation.

REGULATIONS

REGULATIONS

Directiva 2014/35/UE LVD;Directiva 2011/65/UE RoHS;EN 50581:2012;EN 60670-1:2005;EN 60670-1:2005 A1:2013;IEC 60884-1 Ed 3.2;

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053195789

UNITARY PACKAGING WEIGHT

UNIT

KGM

PACKAGING MEASUREMENT

UNIT

MMT

UNITARY PACKAGING HEIGHT

0

PACKAGING EAN

8421053195789

PACKAGING VOLUME

3384375

UNITARY PACKAGING WIDTH

0

UNITS CONTAINED PACKAGING

1

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING LENGTH

0

PACKAGING HEIGHT

285

PACKAGING GROSS WEIGHT

0

UNITARY PACKAGING VOLUME

0

PACKAGING WIDTH

125

PACKAGING NET WEIGHT

0.83

UNITARY PACKAGING GROSS WEIGHT

0.83

PACKAGING LENGTH

95

PACKAGING WEIGHT UNIT

KGM

PRODUCT NET WEIGHT

0.83