

Linear Light module 860 1600 3000 K

REF. 86002300-383



BASIC INFORMATION

APPLICATION

Residential

PACKAGING CONTENTS

1 unit

ETIM CLASS

EC000996

TECHNICAL INFORMATION

FREQUENCY

50 - 60 Hz

VOLTAGE (V~)

220/240 V~

LUMENS/W

116 lm/W

IP RATING

IP20

COLOR TEMPERATURE (K)

3000K

MACADAM STEPS

< 3 Step MacAdam

OPERATING TEMPERATURE RANGE (°C)

Ta Max 35°C

CONTROL

DALI

OPTICS

Opal

POWER SUPPLY (V~)

220/240 V~

CRI

80

POWER (W)

24 W

LUMENS (LM)

2788 lm

REGULATIONS

EAC MARKED

No

ECORRAE MARKED

No

WARRANTY

5 years

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053298930

UNITARY PACKAGING HEIGHT

60

UNITARY PACKAGING WIDTH

60

UNITARY PACKAGING LENGTH

1615

UNITARY PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING VOLUME

5814000

UNITARY PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING GROSS WEIGHT

1.3

PRODUCT NET WEIGHT

0.94

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053298930

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

60

PACKAGING WIDTH

60

PACKAGING LENGTH

1615

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

5814000

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

1.3

PACKAGING NET WEIGHT

0.94

PACKAGING WEIGHT UNIT

KGM